

WHATCOM COUNTY
Planning & Development Services
5280 Northwest Drive,
Bellingham, WA 98226-9097
360-778-5900, TTY 800-833-6384
360-778-5901 Fax



Mark Personius, AICP
Director

PRE2023-00097 ABC Recycling

Commercial Building Permit Application Building # 1
One Structure per Permit

Permit # _____

Agent/Contact Name: _____

Mailing Address: _____ City _____

State _____ Zip Code _____ Phone # () _____

Email _____

Property Owner Name _____

Mailing Address: _____ City _____

State _____ Zip Code _____ Phone # () _____

Email _____

Contractor Name _____

Business Name: _____ License#: _____

Mailing Address: _____ City _____

State _____ Zip Code _____ Phone # () _____

Email _____

Site Information

Assessor's Parcel # _____ Div# _____ Block# _____ Lot# _____

Subdivision Name: _____

Site address _____

Number of Buildings currently on site: _____

Valuation (cost of completed project less value of land) \$ _____

Project Description (example: New 2400 sq. ft. Warehouse w/ office space)

New Addition Remodel Repair Change of Occupancy Tenant Improvement

Building Height: (in feet) _____ # of Stories: _____ # Employees: _____ # Parking Spaces: _____

Company Vehicles: _____ Note: # of employees/parking spaces & vehicles are for entire complex

Please Check Applicable Water & Sanitary Services: Water: Well Water Assoc.

Water District Name of Water Purveyor (if applicable): _____

Fees will be assessed in accordance with the Whatcom County Unified Fee Schedule (UFS) in effect at the time of application submittal. Please contact Planning and Development Services to determine project specific fees. Click [here](#) to see the 2019/2020 UFS. Per UFS 2843 all permits and applications are subject to a Technology fee. The fee is calculated on the permit/application fees due.

Septic: Yes No / Septic Installed: Yes No

Sewer: Yes No Name of Sewer Purveyor (if applicable):

Proposed Square Footages for this project (measured to outside wall):

Basement	sq.ft.	Main Floor	sq.ft.
Basement Type: <input type="checkbox"/> Heated <input type="checkbox"/> Unheated		Second Floor	sq.ft.
Other:	sq.ft.	Total Square Feet	sq.ft.

Heat Source (Check the primary fuel source for Heat / Hot Water)

Heating: Natural Gas Propane Electric Oil Geothermal Other

Hot Water: Natural Gas Propane Electric Oil Geothermal Other

Driveway Access and Utility Connection (work within the county right-of-way)

Does your project involve any work within the County road right-of-way (example: a new driveway or connection to utilities)? Yes No

If yes, please describe: _____

Please note: If upon inspection PW Encroachment staff determines an additional Encroachment Permit is required; you will be notified and received an invoice for the fees.

List materials used in the process of business activity (be specific & list quantities used or stored)

Any proposed fill, excavation or clearing must be noted below *

FILL The deposit of earth material by artificial means.						
BY FEET	Length (ft)	Width (ft)	Depth (ft)	Volume (ft ³)	÷ By 27	= Cubic Yard
Septic	X	X	=		/ 27 =	CY
Driveway/Road/Parking	X	X	=		/ 27 =	CY
Building site	X	X	=		/ 27 =	CY
Other (Total Project Area)	X	X	=		/ 27 =	CY
MATERIAL SOURCE:					TOTAL VOLUME:	CY

EXCAVATION The mechanical removal of earth materials. Grading is an excavation or filling or combination thereof. Earth material is any rock, natural soil, fill, or any combination thereof.						
BY FEET	Length (ft)	Width (ft)	Depth (ft)	Volume (ft ³)	÷ By 27	= Cubic Yard
Septic	X	X	=		/ 27 =	CY
Driveway/Road/Parking	X	X	=		/ 27 =	CY
Building site	X	X	=		/ 27 =	CY
Ditching/Trenching	X	X	=		/ 27 =	CY
Other (Total Project Area)	X	X	=		/ 27 =	CY
MATERIAL DESTINATION:					TOTAL VOLUME:	CY

* Cut/Fill for Building #1 and overall SITE. Cut/fill for other, individual buildings are included with permits for those buildings.

CLEARING/CONVERSION	Defined as, "the destruction of vegetation by manual, mechanical, or chemical methods resulting in exposed soils. WCC20.97.053				
Required TOTAL AREA TO BE CLEARED and/or GRUBBED, IN ACRES:					
AREA OF TREE CLEARING, IN ACRES:					
TIMBER USE	Personal Use:	% Sell:	% Burn:	% Give Away:	%
FPA NUMBER (if applicable)					
If your project includes any tree cutting, a Forest Practices Application / Notification may be required. For questions related to permit requirements, contact the Washington Department of Natural Resources (DNR) at 360-856-3500.					

RECEIVED
Date: 10/24/2023 Staff: AHK

Please complete the following Agent Authorization only if an agent (someone other than the property owner) is applying for permit(s) on the property owner's behalf.

Agent Authorization

If you are authorizing an agent to apply for permits on your behalf you must complete this form and have it notarized, which will provide authorization for a designated agent to apply for permits on your behalf.

I/we, ABC RECYCLING REalty CORP., the owner(s) of the subject property, understand by completing this form I/we hereby authorize Scott Goodall to act as agent. I/we understand said agent will be authorized to submit applications on my behalf, and any fees associated with submitted applications are due to me and not to the said agent. I/we also understand once an application has been submitted all future correspondence will be directed to the agent.

ANDREW ANTHONY
Property Owner Printed Name

Property Owner Printed Name

[Signature]
Property Owner Signature

Property Owner Signature


10/04/2023
Date

Date

I certify that I know or have satisfactory evidence that Andrew Anthony is/are the person(s) who appeared before me, and said person(s) acknowledged it to be his/her free and voluntary act for the uses and purposes mentioned in this instrument.

Dated 10/04/2023

[Signature]
Notary Public Signature



Kendra I Hawkins
Notary Public Printed Name
Notary Public in and for the State of Washington
Residing at Whatcom Co.
My appointment expires: Aug/ 18/ 2025

Disclaimer

The permittee verifies, acknowledges and agrees by their signature that:

- 1) If this permit is for installation of a dwelling, the dwelling is/will be served by potable water;
- 2) The property owner is the owner of this Whatcom County Permit;
- 3) The signatory is the property owner or someone who has permission to represent the property owner in this transaction;
- 4) All construction is to be done in accordance with Whatcom County codes or ordinances- *referenced codes and ordinances are available for review at Whatcom County Planning and Development Services;*
- 5) This Whatcom County Permit does not permit or approve any violation of federal, state or local laws, codes or ordinances;
- 6) Submission of plans or additional information and subsequent approval may be required before this application can be processed;
- 7) Notwithstanding that this application has been submitted in the name of a company, I personally guarantee payment (or guarantee payment on behalf of the client I am representing, noted on the Agent Authorization Form above) of the fees accrued according to the terms listed in the Whatcom County Unified Fee Schedule, including the Application of Fees from Different UFS Schedule Policy PL1-74-003Z, and agree to be bound personally as a principal and not as a surety. I recognize my personal guarantee is part of the consideration for review of the application.

Scott Goodall
Print Name

[Signature]
Owner or Agent Signature

10/21/23
Date

ABC RECYCLING BUILDING 1 OFFICE/SHOP

741 MARINE DRIVE, Bellingham, WA

PROJECT CRITERIA

GENERAL SITE INFORMATION:

ADDRESS: 741 MARINE DRIVE, BELLINGHAM WA
 PARCEL #S: 3802231063740000

CLAIM DAF-BEG ON SLY LI OF MARIETTA RD 992.4 FT S-613.2 FT E OF NW COR SEC 23 BEING COR COMM TO SECS 14-15-22-23-TH S 25 DEG 50'00" W 1170 FT M/L TO GOVT MEANDER LI OF BELLINGHAM BAY-TH SELY FOL SD MEANDER LI TO SE COR OF NEIGHBORHOOD:
 SUB AREA: 2
 ZONING: HEAVY IMPACT INDUSTRIAL

PROJECT DESCRIPTION/WORK TO BE PERFORMED:

NEW CONSTRUCTION OF A PRE ENGINEERED METAL BUILDING

GENERAL BUILDING INFORMATION:

TYPE OF CONSTRUCTION: IIB
 NUMBER OF STORIES: 1 STORY
 OCCUPANCY CLASSIFICATION(S): S1
 MIXED OCCUPANCY
 COMPLIANCE METHODS: FIRE PROTECTED SEPARATIONS
 SPRINKLER SYSTEM: NOT PROVIDED
 ALLOWABLE BUILDING HEIGHT: 32'-3.25"
 ACTUAL BUILDING HEIGHT: 32'-3.25"
 HEAT TYPE: NON HEATED

SITE COVERAGE INFORMATION

SEE CIVIL PLANS

PARKING REQUIREMENTS: (TOTAL PROJECT)

1 PER EMPLOYEE/SHIFT = 15 PER SHIFT =15 STALLS

PARKING PROVIDED =18 STALLS INCL. 2 H.C.

DEFERRED SUBMITTAL ITEMS:

- PRE FAB STEEL BUILDING PLANS & ENGINEERING

APPLICABLE BUILDING CODES:

2018 INTERNATIONAL BUILDING CODE AND AMENDMENTS – CHAPTER 51-50 WAC
 2018 INTERNATIONAL MECHANICAL CODE AND AMENDMENTS – CHAPTER 51-52 WAC
 2018 INTERNATIONAL FUEL GAS CODE AND AMENDMENTS – CHAPTER 51-52 WAC
 2018 INTERNATIONAL ENERGY CONSERVATION CODE (WECC) AND AMENDMENTS – CHAPTER 51-11C & 51-11R WAC
 2017 NATIONAL FUEL GAS CODE (NFPA 54) – CHAPTER 51-52 WAC
 2018 UNIFORM PLUMBING CODE (UPC) AND AMENDMENTS – CHAPTERS 51-56, 51-57 WAC
 2020 NATIONAL ELECTRIC CODE (NFPA 70) – CHAPTER 296-46B WAC
 2018 INTERNATIONAL FIRE CODE (IFC) AND AMENDMENTS – CHAPTER 51-54 WAC
 THE IFC IS ADOPTED AND AMENDED PER REGULATIONS SET FORTH IN BMC 17.20.

ALLOWABLE AREA (PER IBC TABLE 506.2) (MOST RESTRICTIVE USE):

BASIC AREA ALLOWANCE NS, IIB, (F2) =17500 SF PER FLOOR

ACTUAL AREA =6294 SF

BASIC STORY ALLOWANCE NS, IIB, (F2) =2 STORIES

ACTUAL STORY =1 STORY

BUILDING COMPLIES WITH AREA AND STORIES

OCCUPANT LOADS (IBC 1004.1.2):

OCCUPANT LOAD 200 SF (GROSS) = 6294/200 =31 OCC.

DRAWING SHEET LIST

Sheet List	
Sheet Number	Sheet Name
A1.0	Cover Sheet
A1.1	General Notes
A1.3	Site Plan
A2.0	Floor Plan
A3.0	Elevations
A3.2	Perspective Views
A4.0	Building Section
A5.0	Roof & RCP Plan

STRUCTURAL SHEETS:

SEE STRUCTURAL COVER SHEET

BUILDING MANUFACTURER:

SEE MANUFACTURER COVER SHEET

CIVIL SHEETS:

SEE CIVIL COVER SHEET

PROJECT TEAM

ARCHITECT:
 TRC ARCHITECTURE, LLC
 ROBERT MATICHUK
 PO BOX 1075
 BELLINGHAM, WA 98227
 p/f: 360.393.3131



BUILDING JURISDICTION:
 WHATCOM COUNTY
 BUILDING SERVICES
 5280 NORTHWEST DR.
 BELLINGHAM, WA 98226
 360.778.5900

OWNER:
 A B C RECYCLING REALTY CORP
 2219 RIMLAND DR STE 301
 BELLINGHAM, WA 98226-8759

STRUCTURAL ENGINEER:
 Brandon Hausmann, PE
 Principal
 Direct: (360) 474-7541
 Office: (360) 200-8703 ex 1
 203 W. Chestnut St.
 Bellingham WA 98225


GENERAL CONTRACTOR:
 T.B.D.

CIVIL ENGINEER:
 Scott Goodall, MS, PE
 Principal
 Impact Design, LLC
 5426 Barrett Road, Suite A103
 Ferndale, WA 98248
 (360) 389-8138
 www.bold-impact.com



② Site -Cover Sheet
 1" = 80'-0"

I HEREBY CERTIFY THAT THIS DOCUMENT, CONSISTING OF PLANS, DESIGN AND SPECIFICATIONS WAS PREPARED UNDER MY PERSONAL SUPERVISION AND MEET THE CURRENT EDITION OF THE IBC/CBC CODE. ALL PLANS & CALCULATIONS MEET THE GENERALLY ACCEPTED STANDARDS OF PRACTICE WITHIN THE STATE OF WASHINGTON.
 ALL IDEAS, DESIGN AND PLANS INDICATED IN THESE DRAWINGS ARE OWNED AND THE PROPERTY OF TRC ARCHITECTURE. ANY REPRODUCTION OF THESE PLANS MUST HAVE WRITTEN PERMISSION FROM TRC ARCHITECTURE. WRITTEN DIMENSIONS SHALL PRECEDE OVER SCALED DIMENSIONS. CONTRACTOR SHALL VERIFY DIMENSIONS IN THE FIELD AND NOTIFY TRC ARCHITECTURE OF ANY VARIATIONS. CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE IBC/CBC CODE.



Custom Design For: ABC RECYCLING
 Building 1 Office/Shop
 741 Marine Dr
 Bellingham WA 98226

Project number	TRC 22-001
Date	Oct 20 2023
Design	RKM
Drawn by:	RKM
Checked by:	RKM
Set Description:	Permit Set

Cover Sheet

A1.0

ABBREVIATIONS	
A	ADJACENT
A.F.F.	ABOVE FINISH FLOOR
A.F.G.	ABOVE FINISH GRADE
B	BLOCKING
B.L.K.	BOTTOM OF
C	CENTERLINE
CL	CLEAR
CL.G	CEILING
CONC	CONCRETE
COL	COLUMN
CONT	CONTINUOUS
CONST	CONSTRUCTION
CTR	COUNTER
D	DETAIL
DTL	DIMENSION
DWG	DRAWING
E	ELECTRICAL
ELEC	EQUAL
EQ	EXISTING
EXSTG	ENGINEER
ENG	
F	FINISH FLOOR
F.F.	FURNISHED BY CONTRACTOR
F.C.I.C	INSTALLED BY CONTRACTOR
F.O.I.C	FURNISHED BY OWNER
F.O.I.O	INSTALLED BY CONTRACTOR
F.O.I.O.	FURNISHED BY OWNER
F.R.	FIRE RESISTANT
F.E.	FIRE EXTINGUISHER
FBGL	FIBERGLASS
F.O.W.	FACE OF WALL
G	GAUGE
GA	GENERAL CONTRACTOR
G.C.	GLUE LAMINATE
GLAM	GYPSUM WALL BOARD
GYPBD	
H	HARDWARE
HDWR	HEADER
HDR	HOLLOW METAL
H.M.	HEIGHT
HGT	
I	INSTALL / INSTALLED
INST.	INSULATION
INSUL.	
M	MATERIAL
MAT	MECHANICAL
MECH	MICRO LAMINATE WOOD
MLV	MINIMUM
MIN.	
N	NOT APPLICABLE
N/A	NOT IN CONTRACT
N.I.C.	NOT TO SCALE
N.T.S.	
P	PLATE LINE
PL	PLYWOOD
PLYWD	PARALLEL LAMINATE WOOD
P-LAM	PRESSURE TREATED
PT	
R	REQUIRED
REQ'D	REVISION/REVISED
REV.	
S	SCHEDULE
SCH'D	SIMILAR
SIM	SLAB ON GRADE
S.O.G.	SQUARE FOOT
SQ.FT.	SUSPENDED
SUSP.	
T	TEMPERED
TEMP	TYPICAL
TYP	TOP OF
T.O.	
V	VERIFY IN FIELD
V.I.F.	

CONSTRUCTION NOTES:

- APPLICABLE BUILDING CODES VERIFY LOCAL ZONING AND BUILDING CODES PRIOR TO BEGINNING CONSTRUCTION.
- ALL MECHANICAL (INCL. FIRE SPRINKLERS), ELECTRICAL AND PLUMBING BID-DESIGN UNDER SEPARATE PERMIT TO COMPLY WITH ALL APPLICABLE LOCAL CODES.
- DO NOT SCALE DRAWINGS. CONSULT BUILDING DESIGNER AND OWNER FOR ANY DIMENSIONAL CLARIFICATIONS, ERRORS OR CONFLICTS. FLOOR PLANS TAKE PRECEDENCE OVER ELEVATIONS IF CONFLICTING. GENERAL CONTRACTOR MUST VERIFY DIMENSIONS PRIOR TO PROCEEDING.
- GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR ALL COORDINATION OF WORK BETWEEN SUB-CONTRACTOR TRADES, AND FOR PROVIDING WEATHER-TIGHT SEALS, FLASHING AND CAULKING AT ALL CONNECTIONS AND PENETRATIONS. REFER TO IBC CHAPTER 11 FOR MINIMUM WEATHER PROTECTION REQMTS., INCLUDING, BUT NOT LIMITED TO, HEAD FLASHING AT ALL OPENINGS.
- PROVIDE ENGINEERED SHOP DRAWINGS FOR ALL TRUSSES, TRUSS TYPE JOISTS, STEEL BEAMS AND GLU-LAM BEAMS. SUBMIT TO ENGINEER FOR REVIEW.
- THESE DRAWINGS ARE BID-DESIGN DOCUMENTS. THE OWNER/DEVELOPER AND CONTRACTOR SHALL ASSUME RESPONSIBILITY, LIABILITY AND INDEMNIFY THE BUILDING DESIGNER FOR COORDINATION OF BID-DESIGN WORK, INCLUDING BUT NOT LIMITED TO GENERAL CONSTRUCTION, ELECTRICAL, PLUMBING, HEATING AND VENTILATION. THE BUILDING DESIGNER IS NOT LIABLE FOR CHANGES/CORRECTIONS MADE BY ON SITE INSPECTION DURING THE COURSE OF CONSTRUCTION OR FOR DETAILS AND SPECIFICATIONS NOT INCLUDED.
- THE CONTRACTOR SHALL UTILIZE CONSTRUCTION TECHNIQUES AND PRACTICES STANDARD AND ACCEPTABLE TO THE CONSTRUCTION INDUSTRY. THE BUILDING DESIGNER DOES NOT ASSUME LIABILITY OR RESPONSIBILITY FOR METHODS OF CONSTRUCTION DETAILS & SPECIFICATIONS NOT INCLUDED IN THESE BUILDING PERMITS ONLY CONTRACT DOCUMENTS.
- THE BUILDING DESIGNER HAS NOT BEEN RETAINED OR COMPENSATED TO PROVIDE DESIGN AND/OR CONSTRUCTION REVIEW SERVICES RELATING TO THE CONTRACTOR'S SAFETY PRECAUTIONS OR TO MEANS, METHODS, TECHNIQUES OR PROCEDURES REQUIRED FOR THE CONTRACTOR TO PERFORM HIS WORK. THE UNDERTAKING OF PERIODIC SITE VISITS BY THE BUILDING DESIGNER SHALL NOT BE CONSTRUED AS SUPERVISION OF ACTUAL CONSTRUCTION NOR MAKE HIM RESPONSIBLE FOR THE PERFORMANCE OF WORK BY THE CONTRACTOR OR CONTRACTORS EMPLOYEES, OR EMPLOYEES OF SUPPLIERS OR SUBCONTRACTORS, OR FOR ACCESS, VISITS, USE, WORK, TRAVEL OR WORK INJURY BY ANY PERSONEL.
- THESE DOCUMENTS HAVE BEEN PREPARED FOR A NEGOTIATED CONSTRUCTION CONTRACT, AND MAY LACK SOME DETAIL AND SPECIFICATIONS REQUIRED FOR A COMPLETE COMPETITIVE BID SELECTION PROCESS. GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING BUILDING AND SITE SECURITY DURING CONSTRUCTION PERIODS.
- WHERE A CONSTRUCTION DETAIL IS NOT SHOWN OR NOTED, THE DETAIL SHALL BE THE SAME AS FOR OTHER SIMILAR WORK.
- THE CONTRACTOR MUST VERIFY THE ROOF SYSTEM IS CONSTRUCTED PER MANUFACTURERS REQUIREMENTS TO CREATE A WEATHERPROOF AND WATERPROOF ROOF. VERIFY INSTALLATION OF ALL ROOF PENETRATIONS, CURBS, GUTS & FLASHING TO PROPERLY SHED WATER AND STOP WIND DRIVEN RAIN & SNOW. VERIFY ENTIRE ROOF SYSTEM IS DESIGNED & CONSTRUCTED TO ALLOW FOR THE PROPER EXPANSION & CONTRACTION OF THE SUPPORTING STRUCTURE & THE ROOF SYSTEM. CONDENSATION WILL BE CREATED ON THE HEATED SIDE OF ALL ROOF SYSTEMS SURFACES AND PARTS; THEREFORE, CARE MUST BE TAKEN TO PROPERLY INSTALL THE CORRECT INSULATION, VENTILATION AND VAPOR BARRIERS.
- CONTRACTOR IS TO VERIFY STRUCTURAL INFORMATION, SPECIFICATIONS AND DETAILS WITH THE STRUCTURAL ENGINEER AND/OR ATTACHED STRUCTURAL SHEET(S). FAILURE TO VERIFY MAY RESULT IN CONFLICTING INFORMATION CONTAINED ON THE ARCHITECTURAL SHEETS. THE DESIGNER DOES NOT TAKE RESPONSIBILITY FOR STRUCTURAL COMPONENTS OR CALCULATIONS.

FRAMING (STRUCTURAL NOTES TO TAKE PRIORITY)

- THIS STRUCTURE TO COMPLY WITH MINIMUM NAILING SCHEDULE PER ENG. CALCS. OR IBC TABLE 2304.6.1.
- SOLID BLOCKING REQUIRED AT ALL BEARING POINTS OF FLOOR, CEILING & ROOF SYSTEMS.
- PROVIDE APPROVED ANCHORAGE OF BEAMS OR GIRDETS TO POSTS.
- T.J.I. OR EQUIVALENT FLOOR JOISTS. FLOOR JOIST DESIGN BY LICENSED WASH. STATE MANUFACTURER. FLOOR JOIST DESIGN AND SPECIFICATIONS INCLUDING ALL METAL CONNECTORS, HANGERS AND CLIPS TO BE ON-SITE DURING CONSTRUCTION AND INSTALLED AS PER MANF. INSTRUCTIONS.
- ALL WINDOW AND DOOR HEADERS TO BE 4x10 DF-2 IN A ONE-FLOOR OR THE TOP FLOOR OF A MULTI-FLOOR BLD. 6x10 FOR BASEMENTS AND OTHER FLOORS OTHER THAN THE TOP FLOOR. UNLESS NOTED OTHERWISE BY ENGINEER OF RECORD.
- FRAMING LUMBER: KD, 19% MAX MOISTURE CONTENT, S4S GRADE TO W/WPA, AND IRC SPECIFICATIONS. DOUGLAS FIR-LARCH, MINIMUM GRADED STRUSS VALUES: 2x STUDS @ 1200 PSI, JOISTS AND RAFTERS @ 1250 PSI, POSTS A 700 PSI, SAWN BEAMS @ 1300 PSI. NOMINAL SIZES, MAXIMUM SPANS, SPACING, BLOCKING AND OTHER DETAILING IN COMPLIANCE WITH INTERNATIONAL BUILDING CODE.
- PRESSURE TREATED LUMBER: WOLMANIZED, CCA PRESSURE TREATED LUMBER AT MUD SILLS, EXPOSED DECK FRAMING, EXTERIOR STRUCTURAL POSTS, POSTS SUPPORTING MAIN FLOOR STRUCTURE, AND OTHER WOOD / CONCRETE CONTACT LOCATIONS.
- ROOF TRUSSES: FACTORY FABRICATED GANG-NAILED WOOD TRUSSES, ENGINEERED BY MFR. FOR SITE WIND LOADING AND COMBINED NORMAL LOADS SPANS AND CONFIGURATIONS AS SHOWN ON DRAWINGS AND AS REQUIRED.
- GLUE LAMINATED BEAMS (GLB): DOUGLAS FIR, 24F-V4, BUILDING DESIGN RURAL APPEARANCE (ONLY IF EXPOSED) GRADE LEAVE PROTECTIVE WRAP IN PLACE UNTIL FINISH PROCESSES ARE UNDERWAY.
- ANCHORS: SIMPSON PLY CLIPS AT EELS, ROOF SHEATHING PANELS, MID-SPAN BETWEEN RAFTERS OR TRUSSES; TRUSS/PLATE HOLD DOWNS AT EACH BEARING AND OTHER INTERSECTION AS REQUIRED.
- STUDS: EXTERIOR WALL STUDS ARE TO BE 2"x6"s OF B FIR KILN DRIED SPACED AT 16" O.C. INTERIOR STUDS ARE TO BE 2"x4"s OF B FIR KILN DRIED SPACED AT 16" O.C. STUDS IN BEARING WALLS ARE LIMITED TO 10 FEET IN HEIGHT UNLESS APPROVED BY ENGINEER.

STAIRS:

- IBC 1005 & 1011
- IBC 1011.2 STAIRWAY WIDTH. THE WIDTH OF THE STAIRWAYS SHALL BE DETERMINED AS SPECIFIED IN SECTION 1005.1, BUT SUCH WIDTH SHALL NOT BE LESS THAN 44 INCHES. EXCEPTION: STAIRWAYS SERVING AN OCCUPANT LOAD OF LESS THAN 50 SHALL HAVE A WIDTH OF NOT LESS THAN 36 INCHES.
- IBC 1011.3 HEADROOM. STAIRWAYS SHALL HAVE A MINIMUM HEADROOM CLEARANCE OF 80 INCHES MEASURED VERTICALLY FROM A LINE CONNECTING THE EDGE OF THE NOSINGS. SUCH HEADROOM SHALL BE CONTINUOUS ABOVE THE STAIRWAY TO THE POINT WHERE THE LINE INTERSECTS THE LANDING BELOW, ONE TREAD DEPTH BEYOND THE BOTTOM RISER. THE MINIMUM CLEARANCE SHALL BE MAINTAINED THE FULL WIDTH OF THE STAIRWAY AND LANDING.
- IBC 1011.5.2 RISER HEIGHT AND TREAD DEPTH. STAIR RISER HEIGHTS SHALL BE 7 INCHES MAXIMUM AND 4 INCHES MINIMUM. THE RISER HEIGHT SHALL BE MEASURED VERTICALLY BETWEEN THE LEADING EDGES OF ADJACENT TREADS. RECTANGULAR TREAD DEPTHS SHALL BE 11 INCHES MINIMUM MEASURED HORIZONTALLY BETWEEN THE VERTICAL PLANES OF THE FOREMOST PROJECTION OF ADJACENT TREADS AND AT A RIGHT ANGLE TO THE TREAD'S LEADING EDGE. WINDER TREADS SHALL HAVE A MINIMUM TREAD DEPTH OF 11 INCHES MEASURED BETWEEN THE VERTICAL PLANES OF THE FOREMOST PROJECTION OF ADJACENT TREADS AT THE INTERSECTIONS WITH THE WALKLINE AND A MINIMUM TREAD DEPTH OF 10 INCHES WITHIN THE CLEAR WIDTH OF THE STAIR.

DECKS:

- WOOD DECK CONSTRUCTION SHALL BE OF WOLMANIZED / PRESSURE TREATED WOOD. DECKING (SEE PLANS) DECK RAILINGS (REQUIRED IF DECK IS 30" ABOVE GRADE) SHALL BE A MINIMUM OF 42" IN HEIGHT WITH A MAXIMUM OF 4" SPACING BETWEEN PICKETS. PER IBC 1015.
- METAL OR BOLT ON DECK CONSTRUCTION SHALL BE A DEFERRED SUBMITTAL IN ALL CASES.

DISCLOSURE:

- THE PLAN REVIEW GUIDE INCLUDED WITH YOUR PERMIT DOCUMENTS CONTAINS A LISTING OF COMMON CODE ERRORS AND OMISSIONS. APPROVAL OF THE PLANS DOES NOT PERMIT THE VIOLATION OF ANY BUILDING, MECHANICAL, PLUMBING, ELECTRICAL, FIRE, OR ZONING CODE OR ANY OTHER FEDERAL, STATE, OR CITY REGULATIONS.
- CONTRACTOR TO VERIFY LOCATIONS OF EXISTING SMOKE DETECTORS. ENSURE FULL COMPLIANCE WITH CURRENT FIRE CODE.
- CONTRACTOR IS TO SECURE BUILDING SITE/LOCATION. VERIFY STRUCTURAL AND NON-STRUCTURAL COMPONENTS PRIOR TO COMMENCING CONSTRUCTION.
- DO NOT SCALE THESE DRAWINGS. DISCREPANCIES WITH PROVIDED DIMENSIONS MUST BE COMMUNICATED TO THE DESIGN FIRM AT THE EARLIEST CONVENIENCE.
- TRC ARCHITECTURE (DESIGN FIRM) IS NOT RESPONSIBLE FOR EXISTING SITE CONDITIONS, DIMENSIONS, COMPLIANT OR NON-COMPLIANT CODE ISSUES, ETC.
- ALL MARKUPS BY THE BUILDING / PLANNING DEPARTMENTS MUST BE FORWARD TO THE DESIGN FIRM PRIOR TO CONSTRUCTION COMMENCING.

VENTILATION NOTES

1203.1 GENERAL:
BUILDINGS SHALL BE PROVIDED WITH NATURAL VENTILATION IN ACCORDANCE WITH SECTION 1203.4, OR MECHANICAL VENTILATION IN ACCORDANCE WITH THE INTERNATIONAL MECHANICAL CODE.

MECHANICAL VENTILATION IS REQUIRED IN GROUP R OCCUPANCIES

1203.2 ATTIC SPACES:

ENCLOSED ATTICS AND ENCLOSED RAFTER SPACES FORMED WHERE CEILING ARE APPLIED DIRECTLY TO THE UNDERSIDE OF ROOF FRAMING MEMBERS SHALL HAVE CROSS VENTILATION FOR EACH SEPARATE SPACE BY VENTILATING OPENINGS PROTECTED AGAINST THE ENTRANCE OF RAIN AND SNOW. BLOCKING AND BRIDGING SHALL BE ARRANGED SO AS NOT TO INTERFERE WITH THE MOVEMENT OF AIR. A MINIMUM OF 1 INCH OF AIRSPACE SHALL BE PROVIDED BETWEEN THE INSULATION AND THE ROOF SHEATHING. THE NET FREE VENTILATING AREA SHALL NOT BE LESS THAN 1/300 OF THE AREA OF THE SPACE VENTILATED, WITH 50 PERCENT OF THE REQUIRED VENTILATING AREA PROVIDED BY VENTILATORS LOCATED IN THE UPPER PORTION OF THE SPACE TO BE VENTILATED AT LEAST 3 FEET ABOVE EAVE OR CORNICE VENTS WITH THE BALANCE OF THE REQUIRED VENTILATION PROVIDED BY EAVE OR CORNICE VENTS.

EARTHWORK NOTES

- BUILDING BACKFILL: CLEAN GRANULAR SOIL MATERIAL, FREE OF STICKS, DEBRIS, TURF AND ROCKS OVER 6" DIAMETER.
- GARAGE SLAB BALLAST: PIT RUN GRAVEL.
- BASEMENT SLAB BALLAST: CLEAN SAND, OR PEA GRAVEL (8" BED).
- FOOTING DRAINS: WASHED (3/4" MIN.) DRAIN ROCK, 12" MIN. COVER OVER PERIMETER DRAIN.
- CRAWL SPACE BED: PEA GRAVEL OR CLEAN SAND, 2" MIN. BED OVER VAPOR
- 6 MIL BLACK VISQUEEN BARRIER (FOR CRAWL SURFACE).
- BACKFILL, SLOPE ALL FINISH GRADES AWAY FROM BUILDING WALLS AT A 2% (MIN.)
- REFER TO SOILS REPORT FOR RECOMMENDED BACK FILL AND SOIL COMPACTION.

SEWERAGE + DRAINAGE:

- FOUNDATION DRAIN PER IBC 1805.4.2.
- FOUNDATION DISCHARGE TO AN APPROVED DRAINAGE SYSTEM PER IBC 1805.4.3.

ROOF CONSTRUCTION NOTES

GENERAL:

- APPROVED ROOFING MATERIAL
- 30# FELT PAPER, COUNTER FLASHED
- 1/2" CDX PLYWOOD SHEATHING OR PER ENGINEER'S SCHEDULE, USE SIMPSON P/SL (PANEL SHEATHING CLIPS) 1 PER BAY.
- PRE-ENGINEERED TRUSSES
- R-49 INSULATION, MINIMUM.
- 2 LAYERS OF 5/8" TYPE X G.W.B. LID.
- ONE COAT VAPOR BARRIER PRIMER.
- FINISH PAINT - OWNER TO SPECIFY COLOR.
- ROOF PITCH, AS SHOWN ON PLAN.
- SIMPSON CLIPS AT EACH TRUSS/RAFTER TO PLATE CONNECTION.
- TYPICAL SOFFIT OVERHANGS, AS SHOWN ON PLAN. USE VENTED BLOCKING PER TRUSS/RAFTER BAY.
- ADEQUATE CONNECTION AND TRANSFER OF LOAD FROM ROOF SYSTEM TO BEARING WALLS REQUIRED.
- DRAFT STOPS WHERE NECESSARY PER CODE.
- ALL PERIMETER AND BEARING WALL HEADERS TO BE 4x10 DF#2, U.N.O.

TRUSSES:

- TRUSSES TO BE ENGINEERED BY LICENSED TRUSS MANUFACTURER.
- HANG TRUSSES AND RAFTERS WITH APPROVED SIMPSON HANGERS AS PER ENGINEERS SPECIFICATIONS.

FOR ADDITIONAL INFORMATION REFER TO 2015 IBC, SECTION 15, ROOF ASSEMBLIES & ROOFTOP STRUCTURES.

TYPICAL SHEET DISCLAIMER

REFER TO STRUCTURAL SHEETS (S) FOR SPECIFICATIONS & CALCULATIONS. USE ARCHITECTURAL SHEET FOR DIMENSIONAL INFORMATION ONLY.

STRUCTURAL FILL NOTES

STRUCTURAL FILL ADDED TO THIS SITE WHICH WILL SUPPORT BUILDING STRUCTURES SHALL BE APPROVED BY A GEO-TECHNICAL ENGINEER LICENSED TO WORK IN THE STATE OF WASHINGTON. A REPORT FROM SAID ENGINEER REGARDING THE SUITABILITY OF THE PREPARED SITE TO SUPPORT THE PROPOSED STRUCTURE SHALL BE SUBMITTED TO BUILDING SERVICES PRIOR TO ANY REQUESTS FOR FOUNDATION INSPECTION(S).

NOTES:

- CONTRACTOR IS TO VERIFY STRUCTURAL INFORMATION, SPECIFICATIONS AND DETAILS WITH THE STRUCTURAL ENGINEER AND/OR ATTACHED STRUCTURAL SHEET(S). FAILURE TO VERIFY MAY RESULT IN CONFLICTING INFORMATION CONTAINED ON THE ARCHITECTURAL SHEETS. THE DESIGNER DOES NOT TAKE RESPONSIBILITY FOR STRUCTURAL COMPONENTS OR CALCULATIONS.
- REFER TO STRUCTURAL SHEETS (S) FOR SPECIFICATIONS & CALCULATIONS.
- A GEO ENGINEER IS REQUIRED TO BE ON SITE FOR PLACEMENT OF ALL STRUCTURAL FILL MATERIALS.

GENERAL NOTES:

- ALL CONSTRUCTION SHALL COMPLY WITH THE 2018 INTERNATIONAL BUILDING CODE, WASHINGTON STATE REGULATIONS FOR BARRIER FREE DESIGN, WASHINGTON STATE ENERGY CODE, AND ALL APPLICABLE LOCAL CODES, ORDINANCES, AND STANDARDS.
- CONTRACTOR IS TO VERIFY ALL EXISTING CONDITIONS, DIMENSIONAL DETAILS, ETC. AND NOTIFY THE ARCHITECT OF ANY AND ALL DISCREPANCIES PRIOR TO PROCEEDING WITH THE WORK.
- ALL ITEMS MARKED "N.I.C." ARE NOT PART OF THIS CONTACT.
- ALL WORK SHALL BE APPLIED IN ACCORDANCE WITH THE MANUFACTURER'S LATEST RECOMMENDED OR WRITTEN INSTRUCTIONS.
- DO NOT SCALE DRAWINGS, DIMENSIONS GOVERN. THE CONTRACTOR SHALL NOTIFY ARCHITECT IMMEDIATELY OF ANY AND ALL DISCREPANCIES.
- ALL DIMENSIONS ARE TO FACE OF STUD OR CENTER LINE OF STUD, OR FACE OF FOUNDATION WALL UNLESS OTHERWISE NOTED.
- WHEN CONSTRUCTION DETAILS ARE NOT SHOWN OR NOTED FOR ANY PART OF THE WORK, THE DETAILS SHALL BE THE SAME AS FOR OTHER SIMILAR WORK.
- WHERE DEVICES, OR ITEMS OR PARTS THEREOF ARE REFERRED TO IN SINGULAR, IT IS INTENDED THAT SUCH SHALL APPLY TO AS MANY SUCH DEVICES, ITEMS OR PARTS AS ARE REQUIRED TO PROPERLY COMPLETE THE WORK.
- IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO LOCATE ALL EXISTING UTILITIES WHETHER SHOWN HEREON OR NOT AND TO PROTECT THEM FROM DAMAGE.
- THE CONTRACTOR WILL VERIFY AND CONFORM TO ALL REQUIREMENTS OF ALL UTILITY COMPANIES UNLESS OTHERWISE NOTED IN THE PLANS AND SPECIFICATIONS.
- EXISTING ELEVATIONS AND LOCATIONS TO BE JOINED SHALL BE VERIFIED BY THE CONTRACTOR BEFORE CONSTRUCTION.
- THE CONTRACTOR SHALL TAKE ALL NECESSARY PRECAUTIONS TO ENSURE THE SAFETY OF THE OCCUPANTS AND WORKERS AT ALL TIMES.
- CONTRACTOR SHALL SECURE RELEVANT CITY AND STATE APPROVALS RELATING TO FIRE CONSTRUCTION, LABOR, HEALTH AND LICENSING.
- CONTRACTOR SHALL SECURE AND PROVIDE ALL PERMITS FOR OCCUPANCY, UTILITIES AND ANY OTHERS REQUIRED BY LOCAL JURISDICTIONS BEYOND THE BASIC BUILDING PERMIT. MAKING TIMELY APPLICATIONS AND INQUIRES, PAYING ALL FEES AND POSTING ALL BONDS TO BE RELEASED AT FT COMPLETION OF CONSTRUCTION.
- CONTRACTOR SHALL PROVIDE DRAWINGS, SHOP DRAWINGS AND CALCULATIONS AS REQUIRED FOR OWNER APPROVAL AND PERMITTING OF THE FIRE ALARM / MONITORING SYSTEM, AND ALL OTHER SYSTEMS REQUIRING BIDDER DESIGN. SUCH REVIEW AND APPROVAL SHALL BE BY THE OWNER. ALLOW A MINIMUM OF TWO WEEKS FOR REVIEW.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE COMPLETE SECURITY OF THE BUILDING AND SITE WHILE JOB IS IN PROGRESS AND UNTIL THE JOB IS COMPLETED.
- LATHING, PLASTER, AND GYPSUM WALL BOARD SYSTEMS SHALL CONFORM TO THE 2015 INTERNATIONAL BUILDING CODE.
- ALL EXPOSED GYPSUM BOARD TO HAVE METAL EDGES AT ALL CORNERS AND WALL INTERSECTIONS.
- ALL GLASS AND GLAZING SHALL COMPLY WITH SECTION 24 OF THE 2015 IBC, AND THE U.S. PRODUCT SAFETY COMMISSION, SAFETY STANDARD FOR ARCHITECTURAL GLAZING MATERIALS (42 FR 1426; 16 CFR PART 1202)
- THE CONTRACTOR SHALL VERIFY ALL DOOR AND WINDOW ROUGH OPENING DIMENSIONS WITH DOOR AND WINDOW MANUFACTURERS.
- ALL REQUIRED FIRE DOORS SHALL BEAR A LABEL FROM A RECOGNIZED AGENCY SHOWING THE SPECIFIC RATING.
- ELECTRICAL ROUGH-IN, AND REFLECTED CEILING PLAN ARE FOR THE GENERAL INFORMATION OF THE CONTRACTOR. EXACT LOCATIONS SHALL BE VERIFIED.
- EXIT DOORS SHALL BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR ANY SPECIAL KNOWLEDGE OR EFFORT.
- PROVIDE PORTABLE FIRE EXTINGUISHER, EACH HAVING A MINIMUM UL CLASSIFICATION OF 2A-10B-C. EXTINGUISHER SHALL BE DISTRIBUTED THROUGHOUT PREMISES ON THE BASIS OF ONE EXTINGUISHER PER EACH 3,000 FEET OF FLOOR AREA. ALL EXTINGUISHERS SHALL BE HUNG IN CONSPICUOUS LOCATIONS SO THAT THEIR TOPS ARE NOT MORE THAN FIVE FEET A.F.F. WHERE EXTINGUISHERS ARE NOT VISIBLE IN ALL DIRECTIONS PROVIDE APPROVED INDICATING SIGNS.
- SOUND INSULATE ALL PLUMBING WALLS AND LINES.
- PROVIDE BLOCKING IN ALL WALLS TO SUPPORT CABINETRY, SHELVING, BATHROOM FIXTURES, DISPLAY RAILS AND ALL OTHER EQUIPMENT OR IMPROVEMENTS AS REQUIRED.
- THE PREMISES ADDRESS SHALL BE PROMINENTLY DISPLAYED ON OR ADJACENT TO THE MAIN ENTRANCE. NUMBERS SHALL BE A MINIMUM 8 INCHES IN HEIGHT WITH A PRINCIPAL STROKE WIDTH OF 3/4" AND SHALL PROVIDE A POSITIVE CONTRAST WITH THEIR BACKGROUND.
- APPROVED PLANS AND CALCULATIONS, SIGNED, SEALED AND DATED SHALL BE ON SITE AT ALL TIMES OF INSPECTION AND CONSTRUCTION.
- AT ALL TUB/SHOWER LOCATIONS, WALL COVERINGS SHALL BE PLASTIC OR LAMINATE TO A MINIMUM 70 INCHES ABOVE DRAIN.
- ALL SMOKE DETECTORS TO BE HARD WIRED WITH APPROVED BATTERY BACK-UPS ALL GAS APPLIANCES SHALL HAVE AN INTERMITTENT IGNITION DEVICE.
- FLASH AND COUNTER FLASH ALL ROOF TO WALL CONNECTIONS. U.N.O.
- WATERPROOF MATERIAL SHALL BE INSTALLED AROUND TUBS AND SHOWERS TO A MIN. HEIGHT OF SIX FEET ABOVE FINISH FLOOR.
- DRYERS SHALL BE VENTED TO OUTSIDE. PER LOCAL CODE.

CONTRACTOR NOTES

- CONTRACTOR IS TO VERIFY STRUCTURAL INFORMATION, SPECIFICATIONS AND DETAILS WITH THE STRUCTURAL ENGINEER AND/OR ATTACHED STRUCTURAL SHEET(S). FAILURE TO VERIFY MAY RESULT IN CONFLICTING INFORMATION CONTAINED ON THE ARCHITECTURAL SHEETS. THE DESIGNER DOES NOT TAKE RESPONSIBILITY FOR STRUCTURAL COMPONENTS OR CALCULATIONS.

CONCRETE NOTES

REFER TO STRUCTURAL ENGINEERS NOTES

FIRE CODE NOTES

- VERIFY LOCATION OF 110v SMOKE ALARMS & CARBON MONOXIDE ALARMS WITH LOCAL FIRE DEPT. AND/OR LOCAL BUILDING DEPT. ALL SMOKE ALARMS WITHIN INDIVIDUAL UNITS WILL BE INTERCONNECTED.
- BEFORE ANY COMBUSTIBLE CONSTRUCTION BEGINS AN APPROVED WATER SUPPLY SHALL BE AVAILABLE.
- STAIRWELL STANDPIPES SHALL BE INSTALLED WHEN THE PROGRESS OF CONSTRUCTION IS NOT MORE THAN 40 FEET IN HEIGHT ABOVE THE LOWEST LEVEL OF FIRE DEPARTMENT ACCESS.
- FIRE SAFETY DURING CONSTRUCTION SHALL BE PER IFC 2015, CHAPTER 33, ENTITLED "FIRE SAFETY DURING CONSTRUCTION AND DEMOLITION."

FIRE RATED PENETRATIONS

AS PER UL LISTED SYSTEM NO. F-C-2134, USE APPROVED 3M FIRE BARRIER CP 25WB+ CAULK OR FD 150+ CAULK FOR ALL THROUGH FLOOR-WALL-CEILING PENETRATIONS. NOT TO EXCEED 1/2" DIAMETER BEAD CONTINUOUSLY AROUND PIPE.

FIRE BLOCKING NOTES

718.1 General. Fireblocking and draftstopping shall be installed in combustible concealed locations in accordance with this section. Fireblocking shall comply with Section 718.2. Draftstopping in floor/ceiling spaces and attic spaces shall comply with Sections 718.3 and 718.4, respectively.
718.2 Fireblocking. In combustible construction, Fireblocking shall be installed to cut off concealed draft openings (both vertical and horizontal) and shall form an effective barrier between floors, between a top story and a roof or attic space. Fireblocking shall be installed in the locations specified in Sections 718.2.2 through 718.2.7.
718.2.2 Concealed wall spaces. Fireblocking shall be provided in concealed spaces of stud walls and partitions, including furred spaces, and parallel rows of studs or staggered studs, as follows:
1. Vertically at the ceiling and floor levels.
2. Horizontally at intervals not exceeding 10 feet (3048 mm).
718.2.5 Ceiling and floor openings. Where required by Section 712.1.7, Exception 1 of Section 714.4.1.2 or Section 714.4.2, fireblocking of the annular space around vents, pipes, ducts, chimneys and fireplaces at ceilings and floor levels shall be installed with a material specifically tested in the form and manner intended for use to demonstrate its ability to remain in place and resist the free passage of flame and the products of combustion.

* REFER TO IBC CODE TEXT FOR MORE DETAILED INFORMATION REGARDING FIREBLOCKING


DRAFTSTOP NOTES

718.3 Draftstopping in floors. In combustible construction, draftstopping shall be installed to subdivide floor/ceiling assemblies in the locations prescribed in Sections 718.3.2 through 718.3.3.
718.3.2 Groups R-1, R-2, R-3 and R-4. Draftstopping shall be provided in floor/ceiling spaces in Group R-1 buildings, in Group R-2 buildings with three or more dwelling units, in Group R-3 buildings with two dwelling units, and in Group R-4 buildings. Draftstopping shall be located above and in line with the dwelling unit and sleeping unit separations.
Exceptions:
1. Draftstopping is not required in buildings equipped throughout with an automatic sprinkler system in accordance with Section 903.3.1.1.
2. Draftstopping is not required in buildings equipped throughout with an automatic sprinkler system in accordance with Section 903.3.1.2, provided that automatic sprinklers are also installed in the combustible concealed spaces where the draftstopping is being omitted.
718.4 Draftstopping in attics. In combustible construction, draftstopping shall be installed to subdivide attic spaces and concealed roof spaces in the locations prescribed in Sections 718.4.2 and
718.4.2 Groups R-1 and R-2. Draftstopping shall be provided in attics, mansards, overhangs or other concealed roof spaces of Group R-2 buildings with three or more dwelling units and in all Group R-1 buildings. Draftstopping shall be installed above, and in line with, sleeping unit and dwelling unit separation walls that do not extend to the underside of the roof sheathing above.
Exceptions:
1. Where corridor walls provide a sleeping unit or dwelling unit separation, draftstopping shall only be required above one of the corridor walls.
2. Draftstopping is not required in buildings equipped throughout with an automatic sprinkler system in accordance with Section 903.3.1.1.
3. In occupancies in Group R-2 that do not exceed four stories above grade plane, the attic space shall be subdivided by draftstopping into areas not exceeding 3,000 square feet (279 m²) or above every two dwelling units, whichever is smaller.
4. Draftstopping is not required in buildings equipped throughout with an automatic sprinkler system in accordance with Section 903.3.1.2, provided that automatic sprinklers are also installed in the combustible concealed space where the draftstopping is being omitted.

* REFER TO IBC CODE TEXT FOR MORE DETAILED INFORMATION REGARDING FIREBLOCKING

WE HEREBY CERTIFY THAT THIS DOCUMENT, CONSISTING OF PLANS, DESIGN AND SPECIFICATIONS WAS PREPARED UNDER MY PERSONAL SUPERVISION AND MEETS THE CURRENT EDITION OF THE IBC CODE. ALL PLANS & CALCULATIONS MEET THE GENERALLY ACCEPTED STANDARDS OF PRACTICE WITHIN THE STATE OF WASHINGTON.
ALL IDEAS, DESIGN AND PLANS INDICATED IN THESE DRAWINGS ARE OWNED AND THE PROPERTY OF TRC ARCHITECTURE. ANY REPRODUCTION OF THESE PLANS MUST HAVE WRITTEN PERMISSION FROM TRC ARCHITECTURE. WRITTEN DIMENSIONS SHALL HAVE PRECEDENCE OVER SCALED DIMENSIONS. CONTRACTOR SHALL VERIFY DIMENSIONS IN THE FIELD AND NOTIFY TRC ARCHITECTURE OF ANY VARIATIONS. CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE IBC CODE.

www.trcarchitecture.com
PO Box 1075
Bellingham, WA 98227
360.393.3131




Custom Design For: ABC RECYCLING
Building 1 Office/Shop
741 Marine Dr
Bellingham WA 98226

Project number	TRC 22-2001
Date	Oct 20 2023
Design	RKM
Drawn by:	RKM
Checked by:	RKM
Set Description:	
Permit Set	

General Notes

A1.1



I HEREBY CERTIFY THAT THIS DOCUMENT, CONSISTING OF PLANS, DESIGNS AND SPECIFICATIONS WAS PREPARED UNDER MY PERSONAL SUPERVISION AND MEETS THE CURRENT EDITION OF THE B.C.R.C. CODE. ALL PLANS & CALCULATIONS MEET THE GENERALLY ACCEPTED STANDARDS OF PRACTICE WITHIN THE STATE OF WASHINGTON. ALL IDEAS, DESIGN AND PLANS INDICATED IN THESE DRAWINGS ARE OWNED AND THE PROPERTY OF TRC ARCHITECTURE. ANY REPRODUCTION OF THESE PLANS MUST HAVE WRITTEN PERMISSION FROM TRC ARCHITECTURE. WRITTEN DIMENSIONS SHALL HAVE PRECEDENCE OVER SCALED DIMENSIONS. CONTRACTOR SHALL VERIFY DIMENSIONS IN THE FIELD AND NOTIFY TRC ARCHITECTURE OF ANY VARIATIONS. CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE B.C.R.C. CODE.

www.trcarchitecture.com
 PO Box 1075
 Bellingham, WA 98227
 360.393.3131



7852 REGISTERED ARCHITECT


 ROBERT K. MATLOCK
 STATE OF WASHINGTON

Custom Design For: ABC RECYCLING
Building 1 Office/Shop
741 Marine Dr
Bellingham WA 98226


Project number	TRC 22-001
Date	Oct 20 2023
Design	RKM
Drawn by:	RKM
Checked by:	RKM
Set Description:	Permit Set

Site Plan
A1.3

1 Site -Architectural
 1" = 20'-0"



1 Main Floor Plan
1/8" = 1'-0"




2 Main Floor
3/64" = 1'-0"

Door Schedule				
Door Type	Count	Function	Door Size	Type Comments
1	7	Exterior	3/0 7/0 Flush Steel	Insulated metal door and frame, key pad exterior lock, ADA lever latches required
5	2	Exterior	20' x 20' Overhead	W/Locking Pull Chain
Grand total: 9				

I HEREBY CERTIFY THAT THIS DOCUMENT, CONSISTING OF PLANS, DESIGN AND SPECIFICATIONS WAS PREPARED UNDER MY PERSONAL SUPERVISION AND MEETS THE CURRENT EDITION OF THE IBC/CODE. ALL PLANS & CALCULATIONS MEET THE GENERALLY ACCEPTED STANDARDS OF PRACTICE WITHIN THE STATE OF WASHINGTON. ALL IDEAS, DESIGN AND PLANS INDICATED IN THESE DRAWINGS ARE OWNED AND THE PROPERTY OF TRC ARCHITECTURE. ANY REPRODUCTION OF THESE PLANS MUST HAVE WRITTEN PERMISSION FROM TRC ARCHITECTURE. WRITTEN DIMENSIONS SHALL HAVE PRECEDENCE OVER SCALED DIMENSIONS. CONTRACTOR SHALL VERIFY DIMENSIONS IN THE FIELD AND NOTIFY TRC ARCHITECTURE OF ANY VARIATIONS. CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE IBC/CODE.


www.trcarchitecture.com
 PO Box 1075
 Bellingham, WA 98227
 360.393.3131




Custom Design For: ABC RECYCLING
Building 1 Office/Shop
741 Marine Dr
Bellingham WA 98226

Project number	TRC 22-001
Date	Oct 20 2023
Design by	RKM
Drawn by:	RKM
Checked by:	RKM
Set Description:	Permit Set


Floor Plan
A2.0




4 South Elevation
1/8" = 1'-0"



2 West Elevation
1/8" = 1'-0"



3 East Elevation
1/8" = 1'-0"



1 North Elevation
1/8" = 1'-0"

WE HEREBY CERTIFY THAT THIS DOCUMENT, CONSISTING OF PLANS, DESIGN AND SPECIFICATIONS, WAS PREPARED UNDER MY PERSONAL SUPERVISION AND MEETS THE CURRENT EDITION OF THE IBC/CODE. ALL PLANS & CALCULATIONS MEET THE GENERALLY ACCEPTED STANDARDS OF PRACTICE WITHIN THE STATE OF WASHINGTON. ALL IDEAS, DESIGN AND PLANS INDICATED IN THESE DRAWINGS ARE OWNED AND THE PROPERTY OF TRC ARCHITECTURE. ANY REPRODUCTION OF THESE PLANS MUST HAVE WRITTEN PERMISSION FROM TRC ARCHITECTURE. WRITTEN DIMENSIONS SHALL HAVE PRECEDENCE OVER SCALED DIMENSIONS. CONTRACTOR SHALL VERIFY DIMENSIONS IN THE FIELD AND NOTIFY TRC ARCHITECTURE OF ANY VARIATIONS. CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE IBC/CODE.

www.trcarchitecture.com
PO Box 1075
Bellingham, WA 98227
360.393.3131

7852 REGISTERED ARCHITECT
ROBERT K. MATCHUK
STATE OF WASHINGTON

Custom Design For: ABC RECYCLING

Building 1 Office/Shop
741 Marine Dr
Bellingham WA 98226

Project number	TRC 22-001
Date	Oct 20 2023
Design by	RKM
Drawn by	RKM
Checked by	RKM
Set Description:	Permit Set


Elevations
Main Floor 85' - 0"

A3.0

I HEREBY CERTIFY THAT THIS DOCUMENT, CONSISTING OF PLANS, DESIGNS AND SPECIFICATIONS WAS PREPARED UNDER MY PERSONAL SUPERVISION AND MEETS THE CURRENT EDITION OF THE IBC/RC CODE. ALL PLANS & CALCULATIONS MEET THE GENERALLY ACCEPTED STANDARDS OF PRACTICE WITHIN THE STATE OF WASHINGTON.
 ALL IDEAS, DESIGN AND PLANS INDICATED IN THESE DRAWINGS ARE OWNED AND THE PROPERTY OF TRC ARCHITECTURE. ANY REPRODUCTION OF THESE PLANS MUST HAVE WRITTEN PERMISSION FROM TRC ARCHITECTURE. WRITTEN DIMENSIONS SHALL HAVE PRECEDENT OVER SCALED DIMENSIONS. CONTRACTOR SHALL VERIFY DIMENSIONS IN THE FIELD AND NOTIFY TRC ARCHITECTURE OF ANY VARIATIONS. CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE IBC/RC CODE.

www.trcarchitecture.com
 PO Box 1075
 Bellingham, WA 98227
 360.393.3131




7852 REGISTERED ARCHITECT

 ROBERT K. MATICHUK
 STATE OF WASHINGTON

Custom Design For: ABC RECYCLING
Building 1 Office/Shop
741 Marine Dr
Bellingham WA 98226

Project number	TRC 22-001
Date	Oct 20 2023
Design	RKM
Drawn by:	RKM
Checked by:	RKM
Set Description:	Permit Set

Perspective Views
A3.2





① 3D View 1

② 3D View 2

③ 3D View 3

④ 3D View 4



I HEREBY CERTIFY THAT THIS DOCUMENT, CONSISTING OF PLANS, DESIGN AND SPECIFICATIONS, WAS PREPARED UNDER MY PERSONAL SUPERVISION AND MEETS THE CURRENT EDITION OF THE IBC/IRC CODE. ALL PLANS & CALCULATIONS MEET THE GENERALLY ACCEPTED STANDARDS OF PRACTICE WITHIN THE STATE OF WASHINGTON. ALL IDEAS, DESIGN AND PLANS INDICATED IN THESE DRAWINGS ARE OWNED AND THE PROPERTY OF TRC ARCHITECTURE. ANY REPRODUCTION OF THESE PLANS MUST HAVE WRITTEN PERMISSION FROM TRC ARCHITECTURE. WRITTEN DIMENSIONS SHALL HAVE PRECEDENCE OVER SCALED DIMENSIONS. CONTRACTOR SHALL VERIFY DIMENSIONS IN THE FIELD AND NOTIFY TRC ARCHITECTURE OF ANY VARIATIONS. CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE IBC/IRC CODE.


www.trcarchitecture.com
PO Box 1075
Bellingham, WA 98227
360.393.3131

7852 REGISTERED ARCHITECT
ROBERT K. HATCHER
STATE OF WASHINGTON


Custom Design For: ABC RECYCLING
Building 1 Office/Shop
741 Marine Dr
Bellingham WA 98226

Project number	TRC 22-001
Date	Oct 20 2023
Design by:	RKM
Drawn by:	RKM
Checked by:	RKM
Set Description:	Permit Set

Building Section
A4.0



① Roof Plan
1/8" = 1'-0"



② Reflected Ceiling Plan
1/16" = 1'-0"

E-HTH Series

LED Round UFO High Bay Light
Replaces up to 400W PSMH




EHTH3A-HK40UW	13000 Lumens	Neutral White (4000K)	100W	80-CRI	White	250W PSMH
---------------	--------------	-----------------------	------	--------	-------	-----------

③ Lighting - High Bay LED
12" = 1'-0"

WE HEREBY CERTIFY THAT THIS DOCUMENT, CONSISTING OF PLANS, DESIGNS AND SPECIFICATIONS, WAS PREPARED UNDER MY PERSONAL SUPERVISION AND MEETS THE CURRENT EDITION OF THE IBC/CBC CODE. ALL PLANS & CALCULATIONS MEET THE GENERALLY ACCEPTED STANDARDS OF PRACTICE WITHIN THE STATE OF WASHINGTON. ALL IDEAS, DESIGN AND PLANS INDICATED IN THESE DRAWINGS ARE OWNED AND THE PROPERTY OF TRC ARCHITECTURE. ANY REPRODUCTION OF THESE PLANS MUST HAVE WRITTEN PERMISSION FROM TRC ARCHITECTURE. WRITTEN DIMENSIONS SHALL HAVE PRECEDENCE OVER SCALED DIMENSIONS. CONTRACTOR SHALL VERIFY DIMENSIONS IN THE FIELD AND NOTIFY TRC ARCHITECTURE OF ANY VARIATIONS. CONSTRUCTION SHALL CONFORM TO THE CURRENT EDITION OF THE IBC/CBC CODE.

www.trcarchitecture.com
PO Box 1075
Bellingham, WA 98227
360.393.3131




Custom Design For: ABC RECYCLING
Building 1 Office/Shop
741 Marine Dr
Bellingham WA 98226


Project number	TRC 22-001
Date	Oct 20 2023
Design by:	RKM
Drawn by:	RKM
Checked by:	RKM
Set Description:	Permit Set

Roof & RCP
Plan

A5.0



Chief Buildings



ANCHOR ROD PLAN
NOTE: All Base Plates @ 100'-0" (U.N.)

- REFERENCE NOTES:**
- All Anchor Rods including nuts and washers for same are not furnished by CHIEF BUILDINGS.
 - Anchor Rod material shall conform to ASTM F1554 having a yield of 36 KSI or greater.
 - Rod projections are recommended minimums based on the base plate bearing directly on the concrete pier. If the base plate is to bear on grout, the rod projection must be increased accordingly.
 - Concrete shall have a minimum strength of 3000 PSI.
 - ALL DRAWINGS ARE NOT TO SCALE.
 - Anchor Rod Summary Table
 - Quantity includes all buildings, all phases.
 - However anchor rods for Partitions and Smart Canopies are found on separate pages (when applicable).

ANCHOR ROD SUMMARY				
Qty	Locate	Dia (in)	Type	Proj (in)
● 8	Jamb	1/2"	F1554	1.50
⊕ 16	Endwall	3/4"	F1554	2.00
⊕ 64	Frame	3/4"	F1554	2.00

PRELIMINARY


•Preliminary drawings for sales and estimating purposes only.

•Subject to change during order process.

NOT FOR CONSTRUCTION

Drawing	ANCHOR ROD	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A






BASE ANCHORAGE SPACING FOR STANDARD BASE ANGLE, BASE CEE OR ONE PIECE BASE WITH CS OR AP WALLS

FASTENER TYPE & DIAMETER	MINIMUM EMBEDMENT	MAXIMUM SPACING
1/4" WEDGE ANCHOR ①	1 1/4"	3'-0"
1/4" SCREW TYPE ANCHOR ②	1 1/2"	3'-0"
3/8" CAST-IN ANCHOR	4" WITH HOOK OR HEAD	3'-0"
1/4" HAMMER-IN ③	1 3/8"	2'-0"
0.14 POWDER ACTUATED ④	1 1/4"	1'-6"

① HILTI KWIK BOLT®, RAMSET TRUBOLT®, POWERS POWERSTUD®, OR EQUAL
 ② CFS TAPCON®, HILTI KWIK-CON II®, POWERS WEDGE-BOLT®, OR EQUAL
 ③ POWERS ZAMAC HAMMER SCREW®, HILTI METAL HIT ANCHOR®, OR EQUAL
 ④ POWERS BALLISTIC POINT PIN, RAMSET 1500/1600 SERIES, HILTI UNIVERSAL NAIL OR EQUAL

FASTENER SPACING CHART



BASE MEMBER DETAILS
 CONTRACTOR IS RESPONSIBLE FOR ANCHORING BASE MEMBER TO CONCRETE.

REFERENCE NOTES:
 1. ACTUAL BASE PLATE DIMENSIONS MAY BE SMALLER THAN BASE PLATE DIMENSIONS SHOWN.

PRELIMINARY

- Preliminary drawings for sales and estimating purposes only.
- Subject to change during order process.

NOT FOR CONSTRUCTION

Drawing	ANCHOR ROD		
Buyer	Steel Buildings Northwest, Inc		
Customer	ABC Recycling Bellingham, WA 98225		
Project Name	ABC Recycling - bldg 3		
	DATE DRAWN	QUOTE NO.	
	8/25/23	FQ74801A	



RIGID FRAME: BASIC COLUMN REACTIONS (k)

Frame Line	Column Line	Dead	Collateral	Live	Snow	Wind Left	Wind Right
		Horz	Vert	Horz	Vert	Horz	Vert
1*	A	0.0	0.6	0.0	0.1	0.0	0.5
1*	D	0.0	0.6	0.0	0.1	0.0	0.5
1*	B	0.0	1.4	0.0	0.9	0.0	3.5
1*	C	0.0	1.4	0.0	0.9	0.0	3.5

Frame Line	Column Line	Wind Left2	Wind Right2	Wind Long1	Wind Long2	Seismic Left	Seismic Right
		Horz	Vert	Horz	Vert	Horz	Vert
1*	A	-5.9	-7.5	3.8	8.3	2.8	-3.2
1*	D	-3.8	8.3	5.9	-7.5	-2.5	-3.3
1*	B	0.0	2.2	0.0	-12.5	0.0	-4.6
1*	C	0.0	-12.5	0.0	2.2	0.0	-2.0

Frame Line	Column Line	MIN SNOW	F1PAT_LL_1	F1PAT_LL_2	F1PAT_LL_3	F1PAT_LL_4	F1UNB_SL_L
		Horz	Vert	Horz	Vert	Horz	Vert
1*	A	0.0	0.8	0.0	0.4	0.0	-0.6
1*	D	0.0	0.8	0.0	-0.6	0.0	0.4
1*	B	0.0	5.8	0.0	3.6	0.0	2.5
1*	C	0.0	5.8	0.0	2.5	0.0	3.6

Frame Line	Column Line	F1UNB_SL_R	
		Horz	Vert
1*	A	0.0	-0.1
1*	D	0.0	0.7
1*	B	0.0	2.6
1*	C	0.0	5.9

Frame Line	Column Line	Dead	Collateral	Live	Snow	Wind Left	Wind Right
		Horz	Vert	Horz	Vert	Horz	Vert
2*	A	0.5	2.5	1.9	7.5	2.8	10.9
2*	D	-0.5	2.5	-1.9	7.5	-2.8	10.9

Frame Line	Column Line	Wind Left2	Wind Right2	Wind Long1	Wind Long2	Seismic Left	Seismic Right
		Horz	Vert	Horz	Vert	Horz	Vert
2*	A	-10.9	-11.8	3.1	-0.4	3.3	-22.9
2*	D	-3.1	-0.4	10.9	-11.8	-2.8	-20.6

Frame Line	Column Line	Seismic Long	MIN SNOW	F2UNB_SL_L	F2UNB_SL_R
		Horz	Vert	Horz	Vert
2*	A	0.0	-6.0	3.2	12.5
2*	D	0.0	-6.0	-3.2	12.5

1* Frame lines: 1 6
2* Frame lines: 2 3 4 5

- CONTROLLING LOAD CASES**
- 1 Dead+0.6Wind_Left2
 - 2 Dead+0.6Wind_Right2
 - 3 Dead+Collateral+0.75Snow+0.45Wind_Left1+0.75Slide_Snow
 - 4 Dead+Collateral+0.75Snow+0.45Wind_Right1+0.75Slide_Snow
 - 5 0.6Dead+0.6Wind_Left1
 - 6 0.6Dead+0.6Wind_Right1
 - 7 0.6Dead+0.6Wind_Left2
 - 8 0.6Dead+0.6Wind_Right2
 - 9 0.6Dead+0.6Wind_Long1L
 - 10 0.6Dead+0.6Wind_Long2L
 - 11 1.07Dead+1.07Collateral+0.7Seismic_Right
 - 12 Dead+Collateral+MIN_SNOW
 - 13 Dead+Collateral
 - 14 0.6Dead+0.6Wind_Right2+0.6Wind_Suction
 - 15 0.6Dead+0.6Wind_Pressure+0.6Wind_Long2L


BUILDING BRACING REACTIONS

Wall Loc	Col Line	Reactions(k)	Panel Shear (lb/ft)	Note
		Wind Horz	Seismic Vert	
L_EW	1			(h)
F_SW	D	2,3	8.2 9.3 5.3 6.0	
R_EW	6			(h)
B_SW	A	5,4	8.2 9.3 5.3 6.0	


(h) Rigid frame at endwall

Reactions for seismic represent shear force, Eh

FRAME LINES: 1 6



FRAME LINES: 2 3 4 5



RIGID FRAME: MAXIMUM REACTIONS

Frm Line	Col Line	Load Id	Column Reactions(k)		Load Id	Hmin H	Vmin V
			Hmax H	Vmax V			
1*	A	6	3.2	4.2	7	-3.6	-4.1
		2	2.3	5.6	5	-2.7	-5.2
1*	D	8	3.6	-4.1	5	-3.2	4.2
		1	-2.3	5.6	6	2.7	-5.2
1*	B	6	0.0	-7.6	6	0.0	-7.6
		13	0.0	8.2			
1*	C	5	0.0	-7.6	5	0.0	-7.6
		13	0.0	8.2			

1* Frame lines: 1 6

RIGID FRAME: MAXIMUM REACTIONS

Frm Line	Col Line	Load Id	Column Reactions(k)		Load Id	Hmin H	Vmin V
			Hmax H	Vmax V			
2*	A	4	5.4	-0.6	7	-6.2	-5.6
		12	4.2	16.9	9	2.3	-12.2
2*	D	8	6.2	-5.6	3	-5.4	9.6
		12	-4.2	16.9	10	-2.3	-12.2

2* Frame lines: 2 3 4 5

ENDWALL COLUMN: BASIC COLUMN REACTIONS (k)

Frm Line	Col Line	Dead Vert	Wind Press Horz	Wind Suck Horz	Seis Long Horz
1	B	0.4	-6.9	7.6	0.1
1	C	0.4	-6.9	7.6	0.1
6	C	0.4	-6.9	7.6	0.1
6	B	0.4	-6.9	7.6	0.1

ENDWALL COLUMN: MAXIMUM REACTIONS

Frm Line	Col Line	Load Id	Column Reactions(k)		Load Id	Hmin H	Vmin V
			Hmax H	Vmax V			
1	B	14	4.6	0.3	15	-4.2	0.3
		11	0.0	0.5			
1	C	14	4.6	0.3	15	-4.2	0.3
		11	0.0	0.5			
6	C	14	4.6	0.3	15	-4.2	0.3
		11	0.0	0.5			
6	B	14	4.6	0.3	15	-4.2	0.3
		11	0.0	0.5			

1. COLUMN FOOTINGS AND PIERS MUST BE DESIGNED TO WITHSTAND HORIZONTAL AND VERTICAL REACTIONS AS SHOWN ON THE ANCHOR ROD PLAN. CHIEF BUILDINGS IS NOT RESPONSIBLE FOR DESIGN OF CONCRETE FOUNDATION. CHIEF BUILDINGS RECOMMENDS THAT THE SERVICES OF A QUALIFIED ENGINEER IS OBTAINED BY THE CONTRACTOR / BUILDER TO DESIGN THE FOUNDATIONS FOR THE INDICATED REACTIONS.

2. REACTIONS ARE GIVEN IN KIPS. (1 KIP = 1000 LBS.) MOMENTS, IF ANY, ARE GIVEN IN KIP-FT.

3. ANCHOR ROD DESIGN IS BASED ON SHEAR, TENSION, AND COMBINED TENSION AND SHEAR. CHIEF BUILDINGS IS NOT RESPONSIBLE FOR ANCHOR ROD SIZE RECOMMENDATIONS WHEN ANCHOR ROD CONFIGURATION PLACES THE RODS IN A BENDING MODE. WHEN THE COLUMN BASE PLATE BEARS ON GROUT, THE CONTRACTOR / BUILDER OR FOUNDATION ENGINEER SHALL INVESTIGATE BENDING IN THE ANCHOR RODS AND PROVIDE A SHEAR KEY FOR THE COLUMN BASE TO THE PIER WHEN THE ANCHOR RODS ARE NOT ADEQUATE IN BENDING ABOUT THE PIER.

DESCRIPTIONS OF REACTION ABBREVIATIONS

DEAD	DEAD
CL	COLLATERAL
CL ON DEAD	COLLATERAL ON DEAD
CL	LOAD
SL	SLIDE
SNOW	SNOW
SWAY	SWAY
SLIDE	SLIDE
WIND LEFT POSITIVE INTERNAL PRESSURE - WP1	WIND 1 LEFT POSITIVE INTERNAL PRESSURE - WP1
WIND ON WALL_01	WIND 1 LEFT POSITIVE INTERNAL PRESSURE - WP1
WIND ON WALL_02	WIND 2 RIGHT POSITIVE INTERNAL PRESSURE - WP2
WIND ON WALL_03	WIND 3 LEFT POSITIVE INTERNAL PRESSURE - WP3
WIND ON WALL_04	WIND 4 RIGHT POSITIVE INTERNAL PRESSURE - WP4
WIND ON WALL_05	WIND 5 LEFT POSITIVE INTERNAL PRESSURE - WP5
WIND ON WALL_06	WIND 6 RIGHT POSITIVE INTERNAL PRESSURE - WP6
WIND ON WALL_07	WIND 7 LEFT POSITIVE INTERNAL PRESSURE - WP7
WIND ON WALL_08	WIND 8 RIGHT POSITIVE INTERNAL PRESSURE - WP8
WIND ON WALL_09	WIND 9 LEFT POSITIVE INTERNAL PRESSURE - WP9
WIND ON WALL_10	WIND 10 RIGHT POSITIVE INTERNAL PRESSURE - WP10
WIND ON WALL_11	WIND 11 LEFT POSITIVE INTERNAL PRESSURE - WP11
WIND ON WALL_12	WIND 12 RIGHT POSITIVE INTERNAL PRESSURE - WP12
WIND ON WALL_13	WIND 13 LEFT POSITIVE INTERNAL PRESSURE - WP13
WIND ON WALL_14	WIND 14 RIGHT POSITIVE INTERNAL PRESSURE - WP14
WIND ON WALL_15	WIND 15 LEFT POSITIVE INTERNAL PRESSURE - WP15
WIND ON WALL_16	WIND 16 RIGHT POSITIVE INTERNAL PRESSURE - WP16
WIND ON WALL_17	WIND 17 LEFT POSITIVE INTERNAL PRESSURE - WP17
WIND ON WALL_18	WIND 18 RIGHT POSITIVE INTERNAL PRESSURE - WP18
WIND ON WALL_19	WIND 19 LEFT POSITIVE INTERNAL PRESSURE - WP19
WIND ON WALL_20	WIND 20 RIGHT POSITIVE INTERNAL PRESSURE - WP20
WIND ON WALL_21	WIND 21 LEFT POSITIVE INTERNAL PRESSURE - WP21
WIND ON WALL_22	WIND 22 RIGHT POSITIVE INTERNAL PRESSURE - WP22
WIND ON WALL_23	WIND 23 LEFT POSITIVE INTERNAL PRESSURE - WP23
WIND ON WALL_24	WIND 24 RIGHT POSITIVE INTERNAL PRESSURE - WP24
WIND ON WALL_25	WIND 25 LEFT POSITIVE INTERNAL PRESSURE - WP25
WIND ON WALL_26	WIND 26 RIGHT POSITIVE INTERNAL PRESSURE - WP26
WIND ON WALL_27	WIND 27 LEFT POSITIVE INTERNAL PRESSURE - WP27
WIND ON WALL_28	WIND 28 RIGHT POSITIVE INTERNAL PRESSURE - WP28
WIND ON WALL_29	WIND 29 LEFT POSITIVE INTERNAL PRESSURE - WP29
WIND ON WALL_30	WIND 30 RIGHT POSITIVE INTERNAL PRESSURE - WP30
WIND ON WALL_31	WIND 31 LEFT POSITIVE INTERNAL PRESSURE - WP31
WIND ON WALL_32	WIND 32 RIGHT POSITIVE INTERNAL PRESSURE - WP32
WIND ON WALL_33	WIND 33 LEFT POSITIVE INTERNAL PRESSURE - WP33
WIND ON WALL_34	WIND 34 RIGHT POSITIVE INTERNAL PRESSURE - WP34
WIND ON WALL_35	WIND 35 LEFT POSITIVE INTERNAL PRESSURE - WP35
WIND ON WALL_36	WIND 36 RIGHT POSITIVE INTERNAL PRESSURE - WP36
WIND ON WALL_37	WIND 37 LEFT POSITIVE INTERNAL PRESSURE - WP37
WIND ON WALL_38	WIND 38 RIGHT POSITIVE INTERNAL PRESSURE - WP38
WIND ON WALL_39	WIND 39 LEFT POSITIVE INTERNAL PRESSURE - WP39
WIND ON WALL_40	WIND 40 RIGHT POSITIVE INTERNAL PRESSURE - WP40
WIND ON WALL_41	WIND 41 LEFT POSITIVE INTERNAL PRESSURE - WP41
WIND ON WALL_42	WIND 42 RIGHT POSITIVE INTERNAL PRESSURE - WP42
WIND ON WALL_43	WIND 43 LEFT POSITIVE INTERNAL PRESSURE - WP43
WIND ON WALL_44	WIND 44 RIGHT POSITIVE INTERNAL PRESSURE - WP44
WIND ON WALL_45	WIND 45 LEFT POSITIVE INTERNAL PRESSURE - WP45
WIND ON WALL_46	WIND 46 RIGHT POSITIVE INTERNAL PRESSURE - WP46
WIND ON WALL_47	WIND 47 LEFT POSITIVE INTERNAL PRESSURE - WP47
WIND ON WALL_48	WIND 48 RIGHT POSITIVE INTERNAL PRESSURE - WP48
WIND ON WALL_49	WIND 49 LEFT POSITIVE INTERNAL PRESSURE - WP49
WIND ON WALL_50	WIND 50 RIGHT POSITIVE INTERNAL PRESSURE - WP50
WIND ON WALL_51	WIND 51 LEFT POSITIVE INTERNAL PRESSURE - WP51
WIND ON WALL_52	WIND 52 RIGHT POSITIVE INTERNAL PRESSURE - WP52
WIND ON WALL_53	WIND 53 LEFT POSITIVE INTERNAL PRESSURE - WP53
WIND ON WALL_54	WIND 54 RIGHT POSITIVE INTERNAL PRESSURE - WP54
WIND ON WALL_55	WIND 55 LEFT POSITIVE INTERNAL PRESSURE - WP55
WIND ON WALL_56	WIND 56 RIGHT POSITIVE INTERNAL PRESSURE - WP56
WIND ON WALL_57	WIND 57 LEFT POSITIVE INTERNAL PRESSURE - WP57
WIND ON WALL_58	WIND 58 RIGHT POSITIVE INTERNAL PRESSURE - WP58
WIND ON WALL_59	WIND 59 LEFT POSITIVE INTERNAL PRESSURE - WP59
WIND ON WALL_60	WIND 60 RIGHT POSITIVE INTERNAL PRESSURE - WP60
WIND ON WALL_61	WIND 61 LEFT POSITIVE INTERNAL PRESSURE - WP61
WIND ON WALL_62	WIND 62 RIGHT POSITIVE INTERNAL PRESSURE - WP62
WIND ON WALL_63	WIND 63 LEFT POSITIVE INTERNAL PRESSURE - WP63
WIND ON WALL_64	WIND 64 RIGHT POSITIVE INTERNAL PRESSURE - WP64
WIND ON WALL_65	WIND 65 LEFT POSITIVE INTERNAL PRESSURE - WP65
WIND ON WALL_66	WIND 66 RIGHT POSITIVE INTERNAL PRESSURE - WP66
WIND ON WALL_67	WIND 67 LEFT POSITIVE INTERNAL PRESSURE - WP67
WIND ON WALL_68	WIND 68 RIGHT POSITIVE INTERNAL PRESSURE - WP68
WIND ON WALL_69	WIND 69 LEFT POSITIVE INTERNAL PRESSURE - WP69
WIND ON WALL_70	WIND 70 RIGHT POSITIVE INTERNAL PRESSURE - WP70
WIND ON WALL_71	WIND 71 LEFT POSITIVE INTERNAL PRESSURE - WP71
WIND ON WALL_72	WIND 72 RIGHT POSITIVE INTERNAL PRESSURE - WP72
WIND ON WALL_73	WIND 73 LEFT POSITIVE INTERNAL PRESSURE - WP73
WIND ON WALL_74	WIND 74 RIGHT POSITIVE INTERNAL PRESSURE - WP74
WIND ON WALL_75	WIND 75 LEFT POSITIVE INTERNAL PRESSURE - WP75
WIND ON WALL_76	WIND 76 RIGHT POSITIVE INTERNAL PRESSURE - WP76
WIND ON WALL_77	WIND 77 LEFT POSITIVE INTERNAL PRESSURE - WP77
WIND ON WALL_78	WIND 78 RIGHT POSITIVE INTERNAL PRESSURE - WP78
WIND ON WALL_79	WIND 79 LEFT POSITIVE INTERNAL PRESSURE - WP79
WIND ON WALL_80	WIND 80 RIGHT POSITIVE INTERNAL PRESSURE - WP80
WIND ON WALL_81	WIND 81 LEFT POSITIVE INTERNAL PRESSURE - WP81
WIND ON WALL_82	WIND 82 RIGHT POSITIVE INTERNAL PRESSURE - WP82
WIND ON WALL_83	WIND 83 LEFT POSITIVE INTERNAL PRESSURE - WP83
WIND ON WALL_84	WIND 84 RIGHT POSITIVE INTERNAL PRESSURE - WP84
WIND ON WALL_85	WIND 85 LEFT POSITIVE INTERNAL PRESSURE - WP85
WIND ON WALL_86	WIND 86 RIGHT POSITIVE INTERNAL PRESSURE - WP86
WIND ON WALL_87	WIND 87 LEFT POSITIVE INTERNAL PRESSURE - WP87
WIND ON WALL_88	WIND 88 RIGHT POSITIVE INTERNAL PRESSURE - WP88
WIND ON WALL_89	WIND 89 LEFT POSITIVE INTERNAL PRESSURE - WP89
WIND ON WALL_90	WIND 90 RIGHT POSITIVE INTERNAL PRESSURE - WP90
WIND ON WALL_91	WIND 91 LEFT POSITIVE INTERNAL PRESSURE - WP91
WIND ON WALL_92	WIND 92 RIGHT POSITIVE INTERNAL PRESSURE - WP92
WIND ON WALL_93	WIND 93 LEFT POSITIVE INTERNAL PRESSURE - WP93
WIND ON WALL_94	WIND 94 RIGHT POSITIVE INTERNAL PRESSURE - WP94
WIND ON WALL_95	WIND 95 LEFT POSITIVE INTERNAL PRESSURE - WP95
WIND ON WALL_96	WIND 96 RIGHT POSITIVE INTERNAL PRESSURE - WP96
WIND ON WALL_97	WIND 97 LEFT POSITIVE INTERNAL PRESSURE - WP97
WIND ON WALL_98	WIND 98 RIGHT POSITIVE INTERNAL PRESSURE - WP98
WIND ON WALL_99	WIND 99 LEFT POSITIVE INTERNAL PRESSURE - WP99
WIND ON WALL_100	WIND 100 RIGHT POSITIVE INTERNAL PRESSURE - WP100

PRELIMINARY


• Preliminary drawings for sales and estimating purposes only.
• Subject to change during order process.

NOT FOR CONSTRUCTION


Drawing	ANCHOR ROD
Buyer	Steel Buildings Northwest, Inc
Customer	ABC Recycling Bellingham, WA 98225
Project Name	ABC Recycling - bldg 3
DATE DRAWN	8/25/23
QUOTE NO.	FQ74801A



STIFFENER TABLE				
Mark	Stiff Mark	Plate Size		Length
		Width	Thick	
RF1-1	ST1	2.750	0.250	14.94
RF1-2	ST2	2.750	0.250	12.31



RIGID FRAME ELEVATION: FRAME LINE 1 6




PRELIMINARY

- Preliminary drawings for sales and estimating purposes only.
- Subject to change during order process.


NOT FOR CONSTRUCTION

Drawing	CROSS SECTION	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A

STIFFENER TABLE				
Mark	Stiff Mark	Plate Size		Length
		Width	Thick	
RF2-1	ST1	2.750	0.250	26.94



RIGID FRAME ELEVATION: FRAME LINE 2 3 4 5




PRELIMINARY

- Preliminary drawings for sales and estimating purposes only.
- Subject to change during order process.

NOT FOR CONSTRUCTION

Drawing	CROSS SECTION	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A






ROOF FRAMING PLAN

PRELIMINARY

- Preliminary drawings for sales and estimating purposes only.
- Subject to change during order process.

NOT FOR CONSTRUCTION

Drawing	ROOF FRAMING	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A




ROOF SHEETING PLAN
 PANELS: 26 Ga. CS - Std.PVDF-FEVE Finish


PRELIMINARY
 • Preliminary drawings for sales and estimating purposes only.
 • Subject to change during order process.
NOT FOR CONSTRUCTION

Drawing	ROOF SHEETING	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A





SIDEWALL FRAMING: FRAME LINE D



SIDEWALL SHEETING & TRIM: FRAME LINE D

PANELS: 26 Ga. TBD - Std. SMP Finish

GIRT DEPTH: 8.00


PRELIMINARY

- Preliminary drawings for sales and estimating purposes only.
- Subject to change during order process.


NOT FOR CONSTRUCTION

Drawing	SIDEWALL DRAWING	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A





SIDEWALL FRAMING: FRAME LINE A



SIDEWALL SHEETING & TRIM: FRAME LINE A

PANELS: 26 Ga. TBD - Std. SMP Finish

GIRT DEPTH: 8.00


PRELIMINARY

- Preliminary drawings for sales and estimating purposes only.
- Subject to change during order process.


NOT FOR CONSTRUCTION

Drawing	SIDEWALL DRAWING	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A





ENDWALL FRAMING: FRAME LINE 1



ENDWALL SHEETING & TRIM: FRAME LINE 1

PANELS: 26 Ga. TBD - Std. SMP Finish

GIRT DEPTH: 8.00


PRELIMINARY

- Preliminary drawings for sales and estimating purposes only.
- Subject to change during order process.


NOT FOR CONSTRUCTION

Drawing	ENDWALL DRAWING	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A





ENDWALL FRAMING: FRAME LINE 6



ENDWALL SHEETING & TRIM: FRAME LINE 6

PANELS: 26 Ga. TBD - Std. SMP Finish

GIRT DEPTH: 8.00

PRELIMINARY

- Preliminary drawings for sales and estimating purposes only.
- Subject to change during order process.

NOT FOR CONSTRUCTION

Drawing	ENDWALL DRAWING	
Buyer	Steel Buildings Northwest, Inc	
Customer	ABC Recycling Bellingham, WA 98225	
Project Name	ABC Recycling - bldg 3	
	DATE DRAWN	QUOTE NO.
	8/25/23	FQ74801A



SPECIFICATIONS

GENERAL NOTES

- The following notes, details, schedules & specifications shall apply to all phases of this project unless specifically noted otherwise. Notes and details on the structural plans shall take precedence over general notes and typical details. Where no details are given, construction shall be as shown for similar work.
- All drawings are considered to be part of the contract documents. The Contractor shall be responsible for the review and coordination of all drawings and specifications prior to the start of construction. Any discrepancies shall be brought to the attention of the Engineer prior to the start of construction so that a clarification can be issued. Any work performed in conflict with the contract documents or any applicable code requirements shall be corrected by the Contractor at no expense to the Owner or Engineer.
- All information on existing conditions shown on the structural plans are based on best present knowledge available, but without guarantee of accuracy. The Contractor shall be responsible for the verifications of all dimension and conditions at the site. Any discrepancies between actual site conditions and information shown on the drawings or in the specifications shall be brought to the attention of the EOR prior to the start of construction.
- Refer to the Architectural plans for the following:
 - Dimensions
 - Size and location of all interior and exterior wall locations.
 - Size and location of all floor, roof and wall openings
 - Size and location of all drains, slopes, depressions, steps, etc.
 - Specification of all finishes & waterproofing
 - All other non-structural elements
- Refer to the mechanical, electrical and plumbing plans for the following:
 - Size and location of all equipment
 - Pipe runs, sleeves, hangers and trenches
 - All other mechanical, electrical or plumbing related elements
- DO NOT** scale structural plans. Contractor shall use all written dimensions on Architectural plans.
- Construction materials shall be uniformly spread out if placed on floor or roof so as to not overload the framing. Load shall not exceed the design live load per square foot. It is the Contractor's responsibility to provide adequate shoring and/or bracing as required.
- Specifications and detailing of all waterproofing and drainage items, while sometimes shown on the structural plans for general information purposes only, are solely the design responsibility of others.
- The Engineer will not be responsible for and will not have control or charge of construction means, methods, techniques, sequences or procedures, or for safety precautions and programs in connection with the construction delineated by these plans. It should be understood that the Contractor or his/her agent(s) shall supervise and direct all work and shall be solely and completely responsible for all construction means, methods, techniques, sequences, procedures and conditions on the job site, including safety of all persons and property during the entire period of construction. Periodic observations by the Engineer, his staff or representatives are not intended to include verification of dimensions or review the adequacy of the Contractor's safety measures on or near the construction site.
- Modifications to the plans, notes, details and specifications shall not be permitted without prior approval from the Engineer.
- All workmanship shall conform to the best practice prevailing in the various trades performing the work. The Contractor shall be responsible for coordinating the work of all trades.
- It is the Contractor's responsibility to ensure that only approved structural plans are used during the course of construction. The use of unapproved documents shall be at the contractor's own risk. Corrections of all work based on such documents shall be performed at the Contractor's expense.
- These plans and specifications represent the structural design only. No information nor warranty is provided for the work of any other Consultant (Architect, Mechanical, Electrical, etc.). This includes, but is not limited to, waterproofing, drainage, ventilation, accessibility, or dimensions.

FOUNDATIONS

- Refer to Structural Design Parameters section on sheet S-1.1 for all soil design values used in calculations.
- Soils values per to be confirmed by Geotechnical during construction.
- It is the Contractor's responsibility to obtain a copy of the soils report from the Owner. A copy of the soils report shall be on the job site during the course of construction.
- Unexpected Soil Conditions: Allowable values and subsequent foundation designs are based on soil conditions which are shown by test borings. Actual soil conditions which deviate appreciably from that shown in the test borings shall be reported to the Engineer immediately.
- All compaction, fill, backfilling and site preparation shall be performed in accordance with project soils report or the Governing Building Code Chapter 18 & Appendix J. All such work shall be performed per the recommendations of the project soils engineer.
- Excavate to required depths and dimensions (as indicated in the drawings), cut square and smooth with firm level bottoms. Care shall be taken not to over-excavate foundation at lower elevation and prevent disturbance of soils around high elevation.
- Foundations shall be poured in neat excavations.
- Excavate all foundations to required depths into compacted fill or natural soil (as per plans and details) and as verified by the building official and/or soils engineer.
- All foundations shall be inspected and approved by the appropriate building official and/or a representative of the soils engineer prior to forming and placement of reinforcing or concrete.
- Foundations shall not be poured until all required reinforcing steel, framing hardware, sleeves, inserts, conduits, pipes, etc. and formwork is properly placed and inspected by the appropriate building official/inspector(s).
- It is the responsibility of the contractor in charge of framing to properly position all holdown bolts, anchor bolts, column bases, and all other cast-in-place hardware. Refer to typical details. All hardware to be secured prior to foundation inspections.
- The sides and bottoms of dry excavations must be moistened just prior to placing concrete. Conversely, de-water footings as required to remove standing water and to maintain optimum working conditions.
- The Contractor shall be solely responsible for all excavation procedures including lagging, shoring, and the protection of adjacent property, structures, streets, and utilities in accordance with all federal, state and local safety ordinances. The Contractor shall provide for the design and installation of all cribbing, bracing and shoring required.

CONCRETE

- All concrete shall have:
 - an ultimate compressive strength (f_c) of 3,000 psi at 28 days (UNO).
 - a maximum slump of 5" at point of placement
 - a W/C ratio of 0.55 or less for all slabs, walls, and columns, and 0.60 or less for all foundations.
 - a normal dry-weight density (UNO).
- Testing of materials used in concrete construction must be performed as noted on structural plans or at the request of the Building Department to determine if materials are quality specified. Tests of materials and of concrete shall be made by an approved agency and at the expense of the contractor; such tests shall be made in accordance with the standards listed in the Governing Building Code, Table 1704.4. When testing of concrete is required, four (4) test cylinders shall be taken from each 150 yards, or fraction thereof, poured in any one day. One (1) cylinder shall be tested at seven (7) days; two (2) at 28 days; one (1) shall be held in reserve. If Contractor elects to have additional tests performed for "early-break" results, additional test cylinders must be taken. At no time shall the Contractor instruct the testing agency to perform tests on a schedule different than above without the prior authorization of the Engineer. Contractor is responsible for complying with applicable testing requirements of the Building Department. Copies of all test reports shall be provided to Engineer and Building Department for review in a timely manner.
- The Contractor shall remove and replace any concrete which fails to attain specified 28 day compressive strength if so directed by the Engineer. Any defects in the hardened concrete shall be repaired to the satisfaction of the Engineer and/or Architect or the hardened concrete shall be replaced at the Contractor's expense.
- All concrete work shall conform with the Governing Building Code, Chapter 19.
- All cement shall be Portland Cement Type I or II and shall conform to ASTM C 150.
- All aggregates shall conform to ASTM C33. Maximum aggregate sizes:
 - Footings: 1-1/2"
 - All other work: 3/4"
- Where not specifically detailed, the minimum concrete cover on reinforcing steel shall be:
 - Permanently exposed to earth or weather
 - Cast against earth: 3"
 - Cast against forms: 2"
 - Not exposed to earth or weather
 - Slabs, walls, joists: 3/4"
 - Beams, girders, columns: 1-1/2"
- The minimum lap splice length for all reinforcing steel shall be as noted in the typical details on sheet S-1.1. All lap splices to be staggered.
- All reinforcing steel, anchor bolts, dowels, inserts, and any other hardware to be cast in concrete shall be well secured in position prior to foundation inspection. All hardware to be installed in accordance with respective manufacturer's specifications. Refer to architectural and structural plans for locations of embedded items.
- Locations of all construction joints, other than specified on the structural plans, shall be approved by the Architect and Engineer prior to forming. Construction joints shall be thoroughly air and water cleaned and heavily roughened so as to expose coarse aggregates. All surfaces to receive fresh concrete shall be maintained continuously wet at least three (3) hours in advance of concrete placement. Unless specifically detailed or otherwise noted, construction and control joints shall be provided in all concrete slabs-on-grade. Joints shall be located such that the area does not exceed 400 sq. feet.
- The Architect, Engineer and appropriate inspectors shall be notified in a timely manner for a formwork inspection prior to the placement of any concrete.
- The Contractor shall obtain approval from the Architect and the Engineer prior to placing sleeves, pipes, ducts, chases, coring and opening on or through structural concrete beams, walls, floors, and roof slabs unless specifically detailed or noted on the plans. All piles or conduits passing through concrete members shall be sleeved with standard steel pipe sleeves.
- The Contractor is responsible for design, installation, maintenance and removal of all formwork. Forms shall be properly constructed, sufficiently tight to prevent leakage, sufficiently strong, and braced to maintain their shape and alignment until no longer needed for concrete support. Joints in formwork shall be tightly fitted and blocked, and shall produce a finished concrete surface that is true and free from blemishes. Forms for exposed concrete shall be pre-approved by the Architect to ensure conformance with design intent.
- Remove form work in accordance with the following schedule:
 - Forms at slab edge: 1 day
 - Side forms at footings: 2 days
 - All other vertical surfaces: 7 days
 - Beams, columns, girders: 15 days
 - Elevated slabs: 28 days

Engineer reserves the right to modify removal schedule above based on field observations, concrete conditions, and/or concrete test results.
- All concrete (except slabs-on-grade 6" or less) shall be mechanically vibrated as it is placed. Vibrator to be operated by experienced personnel. The vibrator shall be used to consolidate the concrete. The vibrator shall not be used to convey concrete, nor shall it be placed on reinforcing and/or forms.
- Concrete shall be maintained in a moist condition for a min. of five (5) days after placement.
- Concrete shall not be permitted to free fall more than six (6) feet. For heights greater than six (6) feet, use tremie, pump or other method consistent with applicable standards.
- When specified ultimate compressive strength is greater than 2500 psi, Contractor shall submit mix designs to Architect and Engineer for approval seven (7) days prior to placement. Mix designs shall be prepared by an approved testing laboratory. Sufficient data must be provided for all admixtures.
- Refer to Architectural plans for locations of all dimensions, slab depressions, slopes, drains, curbs, and control joints.

REINFORCEMENT


- Reinforcing steel shall be to deformed, clean, free of rust, grease or any other material likely to impair concrete bond.
- All bars shall conform to ASTM A615, Grade 60 minimum (UNO on structural plans). All weld wire fabric (WWF) shall conform to ASTM A185.
- Reinforcing steel that is to be welded shall conform to ASTM A706. All welding of reinforcement shall be subject to special inspection.
- Contractor shall take necessary steps (standard ties, anchorage devices, etc.) to secure all reinforcing steel in their true position and prevent displacement during concrete placement.
- Fabrication, placement and installation of reinforcing steel shall conform to:
 - Concrete Reinforcing Steel Institute (CRSI) Manual of Standard Practice
 - the Governing Building Code, Section 1907.
- Shop drawings for fabrication of reinforcing steel shall be approved by the Contractor and submitted to the Architect and Engineer for review and approval prior to fabrication. Shop drawings are not required for slabs-on-grade or foundations unless specifically noted on the structural plans.
- Heating of reinforcing steel to aid in bending and shaping of bars is not permitted. All bends in reinforcing steel are to be made cold. All bend radii shall conform to CRSI Manual of Standard Practice.
- Refer to Concrete and Masonry notes for specific minimum splice length and splice staggering requirements. Lap welded wire fabric (WWF) reinforcement two (2) modules minimum (UNO). All splices are to be staggered.

ABC Recycling

Building 1 Office / Shop

741 Marine Drive

Bellingham, Washington



The use of these plans and specifications shall be restricted to the original site for which they were prepared and publication thereof is expressly limited to such use. Reproduction or publication by any method, in whole or in part, is prohibited. Title to these plans and specifications remain with Alpine Engineering, LLC, without prejudice. Visual contact with these plans and specifications shall constitute prima facie evidence of the acceptance of these restrictions.



CLIENT:
ABC Recycling
Steven Shim
661 Cornwall Ave.
Bellingham, WA 98225
(360) 472-2880

ARCHITECT / DESIGNER:
Steel Buildings Northwest, Inc.
North Plains, Oregon
(530) 624-7185

SOILS/GEO. ENGINEER:
N/A

DESIGN PARAMETERS
Building Code 2018 IBC*

GENERAL PARAMETERS
Foundation details are subject to change based on the Mfr.'s supplied reactions (Pacific Building Systems, Job # 22-8800, Dated 10/12/2022).
Use of supplied loads & reactions may not be construed as approval of their accuracy or applicability.
No analyses of the pre-engineered metal building (PEMB) members or systems have been performed.

SOILS VALUES
Bearing Pressure (Total Load) * 2000 psf
* To Be Field Verified By Geotechnical

WIND DESIGN BASIS
Wind force analysis has not been performed.
Structural Calculations are based on the Mfr.'s supplied reactions.

SEISMIC DESIGN BASIS
Seismic force analysis of the PEMB has not been performed.
Structural Calculations are based on the Mfr.'s supplied reactions.

* The 2018 International Building Code (IBC) is the governing code in the State of Washington.

Revision:

SHEET INDEX	
S-1.1	Structural Title Sheet
S-2.1	Foundation Plan


Proj. Engr.: S. Williamson
Proj. Mng.: B. Hausmann
Date: 05 Oct. 2023 Scale: NTS
Alpine Eng. Job No.: No. 20004

STRUCTURAL TITLE SHEET

S-1.1

DO NOT SCALE THESE DRAWINGS. Refer to Architectural plans for all dimensions.

STANDARD DETAILS



STANDARD TIES & STIRRUPS


Bar Size	D	H (Approx.)
#3	1-1/2"	3"
#4	2"	3"
#5	2-1/2"	3-3/4"
#6	4-1/2"	4-1/2"
#7	5-1/4"	5-1/4"
#8	6"	6"

STANDARD END HOOKS

Bar Size	D	J
#3	2-1/4"	3"
#4	3"	4"
#5	3-3/4"	5"
#6	4-1/2"	6"
#7	5-1/4"	7"
#8	6"	8"


Note:
All Bar Bend Diameters & End Lengths Must Conform to the CRSI Manual of Standard Practice

STD. DEVELOPMENT LENGTHS & LAP SPLICES






CONCRETE		
Bar Size	Length of Lap, L _d	Embed. of Hook, L _{eh}
#3	16"	21"
#4	22"	28"
#5	27"	35"

TYP. PENETRATION THROUGH FOUNDATION




TYPICAL CONCRETE SLAB JOINTS







1 TYPICAL SLAB ON GRADE




2 EXTERIOR GRADE BEAM FOUNDATION



3 TYPICAL BEAM TO BEAM CONNECTIONS



5 DOOR FRAME ANCHOR BOLTS



4 TYPICAL PERIMETER COL. REINF. PLAN


GENERAL FOUNDATION NOTES

Please see Geotech Recommendations for additional specifications and recommendations. It is the contractor's responsibility to obtain a copy of all geotech info. from the owner or owners representative.

Prior to the contractor requesting a Building Department foundation inspection, the Soils Engineer shall advise the building inspector in writing that:

- Building pad was prepared in accordance with recommendations
- Utility trenches have been properly backfilled and compacted, and
- Foundation excavations, the soil's expansive characteristics and bearing capacity conform to the recommendations

See General Notes & Specifications for additional requirements and material specifications.
All dimensions per Architectural plans
Contractor to VERIFY all dimensions w/ Architectural plans PRIOR to commencement of construction.




SHEAR TIE GRID LOCATIONS

Grid	Tie Spacing & Range
A-2,3,4,5	6" o.c., 2'-0" Ea. Side AB
D-2,3,4,5	6" o.c., 2'-0" Ea. Side AB

Note: All Shear Ties to be #3

ALPINE ENGINEERING, LLC
 203 W. Chestnut
 Bellingham, WA 98225
 (360) 200-8703



www.alpineengineer.com
 CIVIL • STRUCTURAL

The use of these plans and specifications shall be restricted to the original site for which they were prepared and publication thereof is expressly limited to such use. Reproduction or publication by any method, in whole or in part, is prohibited. Title to these plans and specifications remain with Alpine Engineering, LLC, without prejudice. Visual contact with these plans and specifications shall constitute prima facie evidence of the acceptance of these restrictions.



ABC Recycling
 Building 1 Office / Shop
 741 Marine Drive
 Bellingham, Washington

Revision:

Proj. Engr.: S. Williamson
 Proj. Mngr.: B. Hausmann
 Date: 05 Oct. 2023 Scale: NTS
 Alpine Eng. Job No.: No. 20004

STRUCTURAL DETAILS
S-2.1

DO NOT SCALE THESE DRAWINGS. Refer to Architectural plans for all dimensions.



ALPINE
ENGINEERING, LLC

203 W. Chestnut
Bellingham, WA 98225

(360) 200-8703
alpineengineer.com

STRUCTURAL CALCULATIONS

PREPARED FOR:

DATE:

October 18, 2023

PROJECT NO.:

20004

PROJECT NAME:

ABC Recycling; Building 1 Office / Shop

PROJECT TYPE:

PEMB Foundation Design

PROJECT ADDRESS:

741 Marine Drive
Bellingham, WA

ARCHITECT:

TRC Architecture
PO Box 1075
Bellingham, WA 98227
(360) 393-3131

PROJECT ENGINEER:

Brandon Hausmann, PE





TABLE OF CONTENTS

DESIGN PARAMETERS

Foundation Layout	1.1
Design Criteria	1.2

FOUNDATIONS

	1.4 – 1.12
Beam on Elastic Foundation	1.4
PEMB Column Reactions & Load Combo	1.7
Uplift Calculations	1.8
Hairpin Tension Calculation	1.8
Anchor Bolt Calculation	1.10




ALPINE
ENGINEERING, LLC

ABC Recycling
Building 1 Office / Shop
741 Marine Drive
Bellingham, Washington

Job No.: No. 20004

Foundation Layout



PROJECT:	BLDG. I OFFICE SHOP
LOCATION:	BELLINGHA, WA
CLIENT:	TRC
ENGR:	BAH
JOB #:	20004
DATE:	10/3/2023



ALPINE
ENGINEERING, LLC

STRUCTURAL DESIGN CRITERIA

STRUCTURAL L ABSTRACT / SCOPE OF WORK:

STRUCTURAL ENGINEERING IS PROVIDED FOR THE ABC RECYCLING BUILDING No. I OFFICE / SHOP LOCATED IN WHATCOM COUNTY WA. THE STRUCTURE IS A I-STORY PRE-ENGINEERED METAL BUILDING (PEMB). FOUNDATION IS A CONTINUOUS PERIMETER CONCRETE GRADE BEAM, PAD AND INTERIOR SLAB-ON-GRADE. FOUNDATION DESIGN IS BASED ON ARCHITECTURAL PLANS PROVIDED BY TRC ARCHITECTS (PROJECT #22-001, DATED SEPT. 29 2023) AND STEEL BUILDINGS NORTHWEST INC. (QUOTE # FQ74801A, DATED 8/25/23.). THE STRUCTURAL SCOPE OF WORK IS FOR THE FOUNDATION ONLY, NO ANALYSIS OF THE SUPERSTRUCTURE OR FUTURE TENANT IMPROVEMENT HAS BEEN PERFORMED; ALL COLUMN REACTIONS ARE PROVIDED BY THE PEMB MANUFACTURER.

GRADE BEAM CALCULATIONS AT GRID L ARE SHOWN AS 3 SEPARATE CALCULATIONS: COMPOSITE SECTION, POSITIVE BENDING AND NEGATIVE BENDING. THE POSITIVE AND NEGATIVE BENDING CALCULATIONS ARE SHOWN FOR REFERENCE AND ARE NOT FAILING AS INDICATED IN THE CALCULATIONS. THE MODELING LIMITATIONS CANNOT SHOW THE COMPLETE PICTURE, AND ARE USED TO GRAPH THE BENDING MOMENTS AT THE WORST CASE POSITIVE (AT THE COLUMN POINT LOADS) AND NEGATIVE (MID WAY BETWEEN COLUMNS) MOMENTS TO DESIGN FOR THE MINIMUM AMOUNT OF REINFORCEMENT REQUIRED AT THOSE POINTS.

GENERAL:

BUILDING DEPARTMENT:	WHATCOM Co.
APPLICABLE BUILDING CODE:	2018 IBC
IMPORTANCE CATEGORY:	II

GRAVITY LOADING:

PER MFR. REACTIONS

SOILS DATA:

GEOTECHNICAL ENGINEER:	NA	
ALLOWABLE BEARING PRESSURE:	2000 PSF	**FIELD VERIFIED
MIN. FROST EMBEDMENT:	18 "	(PER WHATCOM Co.)

PROJECT:	BLDG. 1 OFFICE SHOP
LOCATION:	BELLINGHA, WA
CLIENT:	TRC
ENGR:	BAH
JOB #:	20004
DATE:	10/3/2023



ALPINE
ENGINEERING, LLC

Design Parameters

Code: 2018 IBC

** Please Refer to Structural Specification on S-1.1 for more detailed information*

Foundations:	Concrete	3000 psi
	Rebar (#5 & larger)	60 ksi
	Rebar (#3 & #4)	40 ksi

Note:

The intent of lateral design is to prevent structural failures in the event of seismic activities or high winds, but not to prevent the damage of architectural finishes or systems. The lateral calculations herein conform to the specifications of the current International Building Code (IBC).

These calculations, specifications, details and drawings are instruments of service and are the property of Alpine Engineering, LLC. The information contained herein is for use on the specific project referenced above and shall not be used otherwise without the written authorization of Alpine Engineering, LLC.

Beam on Elastic Foundation

Project File: ABC Bldg 1 Office Shop - [125x50] - Copy.ec6

LIC# : KW-06012917, Build:20.23.08.30

Alpine Engineering, LLC

(c) ENERCALC INC 1983-2023


DESCRIPTION: Grid A & D - Composite Section

CODE REFERENCES


Calculations per ACI 318-14, IBC 2018, CBC 2019, ASCE 7-16
 Load Combinations Used : ASCE 7-16

Material Properties

f'c	=	2.50 ksi	φ Phi Values	Flexure :	0.90
fr = f'c ^{1/2} * 7.50	=	375.0 psi		Shear :	0.750
ψ Density	=	145.0 pcf	β ₁	=	0.850
λ _L Lt Wt Factor	=	1.0			
Elastic Modulus	=	3,122.0 ksi			
Soil Subgrade Modulus	=	250.0 psi / (inch deflection)			
Load Combination	ASCE 7-16				
fy - Main Rebar	=	60.0 ksi	Fy - Stirrups	=	40.0 ksi
E - Main Rebar	=	29,000.0 ksi	E - Stirrups	=	29,000.0 ksi
			Stirrup Bar Size #	=	# 3
			Number of Resisting Legs Per Stirrup	=	2



Beam is supported on an elastic foundation.



Cross Section & Reinforcing Details

Rectangular Section, Width = 24.0 in, Height = 24.0 in

Span #1 Reinforcing....

3-#5 at 3.0 in from Top, from 0.0 to 125.0 ft in this span

3-#5 at 3.0 in from Bottom, from 0.0 to 125.0 ft in this s

Service loads entered. Load Factors will be applied for calculations.

Applied Loads

Beam self weight calculated and added to loads

- Point Load : D = 4.40, Lr = 7.50, S = 12.50, W = 22.90, E = 6.0 k @ 25.0 ft
- Point Load : D = 4.40, Lr = 7.50, S = 12.50, W = 22.90, E = 6.0 k @ 50.0 ft
- Point Load : D = 4.40, Lr = 7.50, S = 12.50, W = 22.90, E = 6.0 k @ 75.0 ft
- Point Load : D = 4.40, Lr = 7.50, S = 12.50, W = 22.90, E = 6.0 k @ 100.0 ft
- Uniform Load : D = 0.07250, L = 0.250 ksf, Tributary Width = 5.0 ft, (slab)

DESIGN SUMMARY

Design OK

Maximum Bending Stress Ratio =	0.720 : 1	Maximum Deflection	
Section used for this span	Typical Section	Max Downward L+Lr+S Deflection	0.000 in
Mu : Applied	64.546 k-ft	Max Upward L+Lr+S Deflection	0.000 in
Mn * Phi : Allowable	89.697 k-ft	Max Downward Total Deflection	0.047 in
Load Combination	+1.20D+1.60S+0.50W	Max Upward Total Deflection	0.005 in
Location of maximum on span	##.### ft		
Span # where maximum occurs	Span # 1		
Maximum Soil Pressure =	1.697 ksf	at	23.61 ft
Allowable Soil Pressure =	2.0 ksf	OK	LdComb: +D+0.750L+0.750S+0.4

Shear Stirrup Requirements

- Between 0.00 to 23.53 ft, Vu < PhiVc/2, Req'd Vs = Not Req'd, use stirrups spaced at 0.000 in
- Between 25.00 to 25.00 ft, PhiVc/2 < Vu <= PhiVc, Req'd Vs = Min 11.5.6.3, use stirrups spaced at 7.333 in
- Between 26.47 to 48.53 ft, Vu < PhiVc/2, Req'd Vs = Not Req'd, use stirrups spaced at 0.000 in
- Between 50.00 to 50.00 ft, PhiVc/2 < Vu <= PhiVc, Req'd Vs = Min 11.5.6.3, use stirrups spaced at 7.333 in
- Between 51.47 to 98.53 ft, Vu < PhiVc/2, Req'd Vs = Not Req'd, use stirrups spaced at 0.000 in
- Between 100.00 to 100.00 ft, PhiVc/2 < Vu <= PhiVc, Req'd Vs = Min 11.5.6.3, use stirrups spaced at 7.333 in
- Between 101.47 to 122.06 ft, Vu < PhiVc/2, Req'd Vs = Not Req'd, use stirrups spaced at 0.000 in

Beam on Elastic Foundation

Project File: ABC Bldg 1 Office Shop - [125x50] - Copy.ec6

LIC# : KW-06012917, Build:20.23.08.30

Alpine Engineering, LLC

(c) ENERCALC INC 1983-2023

DESCRIPTION: Grid A & D - Composite Section

Maximum Forces & Stresses for Load Combinatio

Load Combination	Segment Length	Span #	Location (ft) in Span	Bending Stress Results (k-ft)		
				Mu : Max	Phi*Mnx	Stress Ratio
MAXimum Bending Envelope						
Span # 1		1	###.###	64.55	89.70	0.72
+1.40D						
Span # 1		1	###.###	10.65	89.70	0.12
+1.20D+0.50Lr+1.60L						
Span # 1		1	###.###	15.35	89.70	0.17
+1.20D+1.60L+0.50S						
Span # 1		1	###.###	19.76	89.70	0.22
+1.20D+1.60Lr+L						
Span # 1		1	###.###	30.03	89.70	0.33
+1.20D+1.60Lr+0.50W						
Span # 1		1	###.###	50.45	89.70	0.56
+1.20D+1.60Lr-0.50W						
Span # 1		1	###.###	10.09	89.70	0.11
+1.20D+L+1.60S						
Span # 1		1	###.###	44.13	89.70	0.49
+1.20D+1.60S+0.50W						
Span # 1		1	###.###	64.55	89.70	0.72
+1.20D+1.60S-0.50W						
Span # 1		1	###.###	24.19	89.70	0.27
+1.20D+0.50Lr+L+W						
Span # 1		1	###.###	55.85	89.70	0.62
+1.20D+0.50Lr+L-W						
Span # 1		1	###.###	4.40	89.70	0.05
+1.20D+L+0.50S+W						
Span # 1		1	###.###	60.26	89.70	0.67
+1.20D+L+0.50S-W						
Span # 1		1	###.###	3.54	89.70	0.04
+0.90D+W						
Span # 1		1	###.###	47.17	89.70	0.53
+0.90D-W						
Span # 1		1	###.###	6.36	89.70	0.07
+1.20D+L+0.20S+E						
Span # 1		1	###.###	23.86	89.70	0.27
+1.20D+L+0.20S-E						
Span # 1		1	###.###	2.71	89.70	0.03
+0.90D+E						
Span # 1		1	###.###	17.38	89.70	0.19
+0.90D-E						
Span # 1		1	###.###	0.56	89.70	0.01

Overall Maximum Deflections - Unfactored Lr

Load Combination	Span	Max. "-" Defl	Location in Span	Load Combination	Max. "+" Defl	Location in Span
Span 1	1	0.0471	23.611		0.0000	0.000

Detailed Shear Information

Load Combination	Span Number	Distance 'd'		Vu (k)		Mu (k-ft)	d*Vu/Mu	Phi*Vc (k)	Comment	Phi*Vs (k)	Spacing (in)	
		(ft)	(in)	Actual	Design						Req'd	Suggest
+1.20D+0.50Lr+1.60L	1	0.00	21.00	2.15	2.15	0.00	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+0.50Lr+1.60L	1	1.47	21.00	2.04	2.04	0.10	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+0.50Lr+L-W	1	2.94	21.00	1.97	1.97	0.40	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+0.50Lr+L-W	1	4.41	21.00	2.06	2.06	0.85	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+0.50Lr+L-W	1	5.88	21.00	2.13	2.13	1.44	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+0.50Lr+L-W	1	7.35	21.00	2.15	2.15	2.11	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+0.50Lr+L-W	1	8.82	21.00	2.13	2.13	2.83	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+0.50Lr+L-W	1	10.29	21.00	2.05	2.05	3.51	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+0.50Lr+1.60L	1	11.76	21.00	2.03	2.03	3.32	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+1.60L+0.50S	1	13.24	21.00	2.22	2.22	4.44	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+L+0.50S+W	1	14.71	21.00	2.69	2.69	12.12	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+L+0.50S+W	1	16.18	21.00	4.01	4.01	10.62	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+L+0.50S+W	1	17.65	21.00	5.73	5.73	7.17	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+L+0.50S+W	1	19.12	21.00	7.88	7.88	1.19	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+L+0.50S+W	1	20.59	21.00	10.46	10.46	7.95	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+L+0.50S+W	1	22.06	21.00	13.43	13.43	20.88	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+1.60S+0.50W	1	23.53	21.00	16.77	16.77	40.99	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00
+1.20D+1.60S+0.50W	1	25.00	21.00	20.35	20.35	64.55	1.00	39.40	PhiVc/2 < Vu <= PhiVc	Min 11.5.6.3	0.00	7.33
+1.20D+1.60S+0.50W	1	26.47	21.00	-12.94	12.94	39.36	1.00	39.40	Vu < PhiVc/2	Not Req'd	0.00	0.00

Beam on Elastic Foundation

Project File: ABC Bldg 1 Office Shop - [125x50] - Copy.ec6

LIC# : KW-06012917, Build:20.23.08.30

Alpine Engineering, LLC

(c) ENERCALC INC 1983-2023

DESCRIPTION: Grid A & D - Composite Section

Detailed Shear Information

Load Combination	Span Number	Distance 'd'		Vu (k)		Mu (k-ft)	d*Vu/Mu	Phi*Vc (k)	Comment	Phi*Vs (k)	Spacing (in)	
		(ft)	(in)	Actual	Design						Req'd	Suggest
+1.20D+1.60S+0.50W	1	27.94	21.00	-9.83	9.83	19.24	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	29.41	21.00	-7.14	7.14	3.68	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	30.88	21.00	-4.90	4.90	7.92	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	32.35	21.00	3.11	3.11	5.64	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	33.82	21.00	2.54	2.54	7.76	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	35.29	21.00	2.07	2.07	9.05	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60L+0.50S	1	36.76	21.00	2.23	2.23	8.91	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	38.24	21.00	2.76	2.76	25.31	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	39.71	21.00	3.91	3.91	23.70	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	41.18	21.00	5.27	5.27	20.41	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	42.65	21.00	6.93	6.93	15.11	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	44.12	21.00	8.96	8.96	7.36	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	45.59	21.00	11.39	11.39	3.37	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	47.06	21.00	14.19	14.19	17.67	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	48.53	21.00	17.41	17.41	38.76	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	50.00	21.00	20.84	20.84	63.27	1.00	39.40	PhiVc/2 < Vu <= PhiVc	Min 11.5.6.3	0.00	7.33
+1.20D+1.60S+0.50W	1	51.47	21.00	-12.59	12.59	38.81	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	52.94	21.00	-9.59	9.59	19.20	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	54.41	21.00	-7.00	7.00	4.00	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	55.88	21.00	-4.83	4.83	7.39	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	57.35	21.00	3.10	3.10	5.41	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	58.82	21.00	2.55	2.55	7.52	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	60.29	21.00	2.08	2.08	8.81	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+1.60L	1	61.76	21.00	2.22	2.22	6.95	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	63.24	21.00	2.71	2.71	24.83	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	64.71	21.00	3.86	3.86	23.30	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	66.18	21.00	5.22	5.22	20.08	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	67.65	21.00	6.89	6.89	14.85	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	69.12	21.00	8.92	8.92	7.17	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	70.59	21.00	11.36	11.36	3.51	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	72.06	21.00	14.16	14.16	17.76	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	73.53	21.00	17.38	17.38	38.81	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	75.00	21.00	-15.92	15.92	63.27	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	76.47	21.00	-12.62	12.62	38.76	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	77.94	21.00	-9.63	9.63	19.11	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	79.41	21.00	-7.04	7.04	3.85	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	80.88	21.00	-4.87	4.87	7.60	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	82.35	21.00	3.12	3.12	5.51	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	83.82	21.00	2.57	2.57	7.65	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	85.29	21.00	2.10	2.10	8.98	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+1.60L	1	86.76	21.00	2.20	2.20	7.07	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	88.24	21.00	2.67	2.67	25.38	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	89.71	21.00	3.84	3.84	23.90	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	91.18	21.00	5.24	5.24	20.70	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	92.65	21.00	6.96	6.96	15.44	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	94.12	21.00	9.06	9.06	7.66	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	95.59	21.00	11.58	11.58	3.21	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	97.06	21.00	14.49	14.49	17.79	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	98.53	21.00	17.87	17.87	39.36	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	100.00	21.00	21.46	21.46	64.55	1.00	39.40	PhiVc/2 < Vu <= PhiVc	Min 11.5.6.3	0.00	7.33
+1.20D+1.60S+0.50W	1	101.47	21.00	-11.80	11.80	40.99	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	102.94	21.00	-8.64	8.64	22.54	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	104.41	21.00	-5.89	5.89	8.74	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60S+0.50W	1	105.88	21.00	-3.59	3.59	1.01	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	107.35	21.00	2.62	2.62	2.31	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+L-W	1	108.82	21.00	2.09	2.09	3.71	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+0.50Lr+1.60L	1	110.29	21.00	2.22	2.22	3.59	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60L+0.50S	1	111.76	21.00	2.44	2.44	4.44	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	113.24	21.00	2.70	2.70	11.29	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	114.71	21.00	2.92	2.92	9.76	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	116.18	21.00	2.99	2.99	7.91	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	117.65	21.00	2.93	2.93	5.97	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	119.12	21.00	2.78	2.78	4.11	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+L+0.50S+W	1	120.59	21.00	2.55	2.55	2.47	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60L+0.50S	1	122.06	21.00	2.44	2.44	0.45	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00
+1.20D+1.60L+0.50S	1	123.53	21.00	2.30	2.30	0.12	1.00	39.40	Vu < PhiVc/2	Not Reqd	0.00	0.00

PROJECT:	ABC BUILDING I OFFICE
LOCATION:	WHATCOM COUNTY, WA
CLIENT:	TRC
ENGR:	BAH
JOB #:	20004
DATE:	10/3/2023



PEMB Column Reactions & Load Combinations

Load Combinations per ASCE 7-10

ASD Load Combinations			LRFD Load Combinations															PEMB Reaction definitions		ASD load combos		
Grid	Coll	Snow	L	E	W (max)	RS	LS	D	Coll	Snow	L	E	W (max)	RS	LS	E	W (max)	Max Horiz	Max Vert	Max OOP		
1	D							1	1.4D									D + Coll	Total Dead Load			
2	D+L							2	1.2D+1.6L+0.5(Lr or S or R)									W+	Wind acting inward			
3	D+(Lr or S or R)							3	1.2D+1.6(Lr or S or R)+(L or 0.5W)									W-	Wind acting outward (suction)			
4	D+0.75L+0.75(Lr or S or R)							4	1.2D+1.0W+L+0.5(Lr or S or R)									E+	Seismic acting inward			
5	D+(0.6W or 0.7E)							5	1.2D+1.0E+L+0.2S									E-	Seismic acting outward			
6a	D+0.75L+0.75(0.6W)+0.75(Lr or S or R)							6	0.9D+1.0W									W (max)	Total concurrent Wind Loading, worst case			
6b	D+0.75L+0.75(0.6E)+0.75S							7	0.9D+1.0E													
7	0.6D+0.6W																					
8	0.6D+0.7E																					

2* Corresponds to Frames at Grids 2,3,4,5

1* Corresponds to Frames at Grids 1,6

PROJECT:	ABC BUILDING I OFFICE
LOCATION:	WHATCOM COUNTY, WA
CLIENT:	TRC
ENGR:	BAH
JOB #:	20004
DATE:	10/3/2023



ALPINE
ENGINEERING, LLC

Wind & Seismic Uplift Calculations:

Grid	PEMB		UPLIFT		ASD UPLIFT		LRFD UPLIFT		Down +	lateral	
	D+Coll	E	W		SEIS	WIND	SEIS	WIND			
1	A	0.7	-1.5	-9.3	20.7	12.9	31.8	24.0	OK	12.9	4.4
2*	A	4.4	1.1	-18.1	23.3	6.3	35.5	18.5	OK	6.3	25
2*	D	4.4	-0.2	-22.9	24.2	1.5	36.4	13.7	OK	1.5	15.4
Conc. Unit Weight			145 lb/cf								
Fdn. Trib Length			30 ft		2* Corresponds to Frames at Grids 2,3,4,5						
Fdn. Depth			24 in		1* Corresponds to Frames at Grids 1,6						
Fdn. Width			25 in								
Slab Trib. Area			250 sf								
Slab Thickness			6 in								
Total Trib. Fdn. Weight =			36.3 kips								

Hairpin Tension Calculations:

fy hairpin =	60 ksi	Area Req'd =	0.463 in ²	USE:	#5 Hairpin OR (2) #4 Hairpins
Max Horiz. Force	25 kip				



Anchor Designer™
Software
Version 3.2.2309.2

Company:		Date:	10/4/2023
Engineer:	BAH	Page:	1/5
Project:	ABC Recycling - Bldg 1 Shop		
Address:			
Phone:			
E-mail:			

1. Project information

Customer company:
Customer contact name:
Customer e-mail:
Comment:

Project description:
Location:
Fastening description:

2. Input Data & Anchor Parameters

General

Design method: ACI 318-14
Units: Imperial units

Anchor Information:

Anchor type: Cast-in-place
Material: AB_H
Diameter (inch): 0.750
Effective Embedment depth, h_{ef} (inch): 18.000
Anchor category: -
Anchor ductility: Yes
 h_{min} (inch): 20.25
 C_{min} (inch): 1.63
 S_{min} (inch): 3.00

Base Material

Concrete: Normal-weight
Concrete thickness, h (inch): 24.00
State: Cracked
Compressive strength, f'_c (psi): 3000
 $\Psi_{c,v}$: 1.0
Reinforcement condition: B tension, B shear
Supplemental edge reinforcement: Not applicable
Reinforcement provided at corners: No
Ignore concrete breakout in tension: No
Ignore concrete breakout in shear: No
Ignore 6do requirement: Yes
Build-up grout pad: No

Base Plate

Length x Width x Thickness (inch): 10.50 x 6.00 x 0.38

Recommended Anchor

Anchor Name: PAB Pre-Assembled Anchor Bolt - PAB6H (3/4"Ø)



Input data and results must be checked for agreement with the existing circumstances, the standards and guidelines must be checked for plausibility.



Anchor Designer™
 Software
 Version 3.2.2309.2

Company:		Date:	10/4/2023
Engineer:	BAH	Page:	2/5
Project:	ABC Recycling - Bldg 1 Shop		
Address:			
Phone:			
E-mail:			


Load and Geometry

Load factor source: ACI 318 Section 5.3
 Load combination: not set
 Seismic design: No
 Anchors subjected to sustained tension: Not applicable
 Apply entire shear load at front row: No
 Anchors only resisting wind and/or seismic loads: No

Strength level loads:

N_{ua} [lb]: 20650
 V_{uax} [lb]: 10900
 V_{uay} [lb]: 0
 M_{ux} [ft-lb]: 0
 M_{uy} [ft-lb]: 0
 M_{uz} [ft-lb]: 0

<Figure 1>




Input data and results must be checked for agreement with the existing circumstances, the standards and guidelines must be checked for plausibility.



Anchor Designer™
 Software
 Version 3.2.2309.2

Company:		Date:	10/4/2023
Engineer:	BAH	Page:	3/5
Project:	ABC Recycling - Bldg 1 Shop		
Address:			
Phone:			
E-mail:			

<Figure 2>





Anchor Designer™
Software
Version 3.2.2309.2


Company:		Date:	10/4/2023
Engineer:	BAH	Page:	4/5
Project:	ABC Recycling - Bldg 1 Shop		
Address:			
Phone:			
E-mail:			

3. Resulting Anchor Forces

Anchor	Tension load, N_{ua} (lb)	Shear load x, V_{uax} (lb)	Shear load y, V_{uay} (lb)	Shear load combined, $\sqrt{(V_{uax})^2 + (V_{uay})^2}$ (lb)
1	9046.7	2725.0	0.0	2725.0
2	9046.7	2725.0	0.0	2725.0
3	2987.6	2725.0	0.0	2725.0
4	2987.6	2725.0	0.0	2725.0
Sum	24068.7	10900.0	0.0	10900.0

Maximum concrete compression strain (%): 0.17
 Maximum concrete compression stress (psi): 746
 Resultant tension force (lb): 24069
 Resultant compression force (lb): 3419
 Eccentricity of resultant tension forces in x-axis, e'_{Nx} (inch): 0.00
 Eccentricity of resultant tension forces in y-axis, e'_{Ny} (inch): 1.01
 Eccentricity of resultant shear forces in x-axis, e'_{Vx} (inch): 0.00
 Eccentricity of resultant shear forces in y-axis, e'_{Vy} (inch): 0.00

<Figure 3>



4. Steel Strength of Anchor in Tension (Sec. 17.4.1)

N_{sa} (lb)	ϕ	ϕN_{sa} (lb)
40080	0.75	30060

5. Concrete Breakout Strength of Anchor in Tension (Sec. 17.4.2)

$$N_b = 16\lambda_a \sqrt{f_c} h_{ef}^{5/3} \text{ (Eq. 17.4.2.2b)}$$

λ_a	f_c (psi)	h_{ef} (in)	N_b (lb)
1.00	3000	18.000	108343

$$\phi N_{cbg} = \phi (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b \text{ (Sec. 17.3.1 \& Eq. 17.4.2.1b)}$$

A_{Nc} (in ²)	A_{Nco} (in ²)	$c_{a,min}$ (in)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕN_{cbg} (lb)
1506.25	2916.00	9.00	0.964	0.800	1.00	1.000	108343	0.70	30213

6. Pullout Strength of Anchor in Tension (Sec. 17.4.3)

$$\phi N_{pn} = \phi \Psi_{c,P} N_p = \phi \Psi_{c,P} 8 A_{brg} f_c \text{ (Sec. 17.3.1, Eq. 17.4.3.1 \& 17.4.3.4)}$$

$\Psi_{c,P}$	A_{brg} (in ²)	f_c (psi)	ϕ	ϕN_{pn} (lb)
1.0	3.53	3000	0.70	59371

Input data and results must be checked for agreement with the existing circumstances, the standards and guidelines must be checked for plausibility.



Anchor Designer™
Software
Version 3.2.2309.2

Company:		Date:	10/4/2023
Engineer:	BAH	Page:	5/5
Project:	ABC Recycling - Bldg 1 Shop		
Address:			
Phone:			
E-mail:			

8. Steel Strength of Anchor in Shear (Sec. 17.5.1)

V_{sa} (lb)	ϕ_{grout}	ϕ	$\phi_{grout}\phi V_{sa}$ (lb)
24050	1.0	0.65	15633

9. Concrete Breakout Strength of Anchor in Shear (Sec. 17.5.2)

Shear perpendicular to edge in x-direction:

$$V_{bx} = \min[7(l_e/d_a)^{0.2}\sqrt{d_a}\lambda_a\sqrt{f'_c}c_{a1}^{1.5}; 9\lambda_a\sqrt{f'_c}c_{a1}^{1.5}] \text{ (Eq. 17.5.2.2a \& Eq. 17.5.2.2b)}$$

l_e (in)	d_a (in)	λ_a	f'_c (psi)	c_{a1} (in)	V_{bx} (lb)
6.00	0.750	1.00	3000	16.00	31549

$$\phi V_{cbgx} = \phi (A_{Vc} / A_{Vco}) \Psi_{ec,V} \Psi_{ed,V} \Psi_{c,V} \Psi_{h,V} V_{bx} \text{ (Sec. 17.3.1 \& Eq. 17.5.2.1b)}$$

A_{Vc} (in ²)	A_{Vco} (in ²)	$\Psi_{ec,V}$	$\Psi_{ed,V}$	$\Psi_{c,V}$	$\Psi_{h,V}$	V_{bx} (lb)	ϕ	ϕV_{cbgx} (lb)
1248.00	1152.00	1.000	1.000	1.000	1.000	31549	0.70	23925

10. Concrete Pryout Strength of Anchor in Shear (Sec. 17.5.3)

$$\phi V_{cbgx} = \phi k_{cp} N_{cbg} = \phi k_{cp} (A_{Nc} / A_{Nco}) \Psi_{ec,N} \Psi_{ed,N} \Psi_{c,N} \Psi_{cp,N} N_b \text{ (Sec. 17.3.1 \& Eq. 17.5.3.1b)}$$

k_{cp}	A_{Nc} (in ²)	A_{Nco} (in ²)	$\Psi_{ec,N}$	$\Psi_{ed,N}$	$\Psi_{c,N}$	$\Psi_{cp,N}$	N_b (lb)	ϕ	ϕV_{cbgx} (lb)
2.0	1506.25	2916.00	1.000	0.800	1.000	1.000	108343	0.70	62680

11. Results

Interaction of Tensile and Shear Forces (Sec. R17.6)

Tension	Factored Load, N_{ua} (lb)	Design Strength, ϕN_n (lb)	Ratio	Status	
Steel	9047	30060	0.30	Pass	
Concrete breakout	24069	30213	0.80	Pass (Governs)	
Pullout	9047	59371	0.15	Pass	
Shear	Factored Load, V_{ua} (lb)	Design Strength, ϕV_n (lb)	Ratio	Status	
Steel	2725	15633	0.17	Pass	
T Concrete breakout x+	10900	23925	0.46	Pass (Governs)	
Pryout	10900	62680	0.17	Pass	
Interaction check	$(N_{ua}/\phi N_{ua})^{5/3}$	$(V_{ua}/\phi V_{ua})^{5/3}$	Combined Ratio	Permissible	Status
Sec. R17.6	0.68	0.27	95.4%	1.0	Pass

PAB6H (3/4"Ø) with hef = 18.000 inch meets the selected design criteria.


12. Warnings

- Minimum spacing and edge distance requirement of 6da per ACI 318 Sections 17.7.1 and 17.7.2 for torqued cast-in-place anchor is waived per designer option.

- Designer must exercise own judgement to determine if this design is suitable.

Input data and results must be checked for agreement with the existing circumstances, the standards and guidelines must be checked for plausibility.

Simpson Strong-Tie Company Inc. 5956 W. Las Positas Boulevard Pleasanton, CA 94588 Phone: 925.560.9000 Fax: 925.847.3871 www.strongtie.com



2050103719

Page: 1 of 4
1/25/2005 11:16 AM
NINT \$22.00
Whatcom County, WA

Request of: BELLINGHAM CITY OF

AFTER RECORDING RETURN DOCUMENT TO:

City of Bellingham - Public Works, Engineering
210 Lottie Street
Bellingham, WA 98225

↑ Reserved for Recording Purposes Only ↑

DOCUMENT TITLE: *Statement of Intent to Collect Connection Fee*

REFERENCE NUMBER OF RELATED DOCUMENT:

GRANTOR(S): *City of Bellingham*

ADDITIONAL GRANTORS ON PAGE ____ OF DOCUMENT.

GRANTEE(S): *City of Bellingham*

ADDITIONAL GRANTEES ON PAGE ____ OF DOCUMENT.

ABBREVIATED LEGAL DESCRIPTION: *Located in a portion of the Southeast 1/4 of section 15, the Northwest 1/4 of Section 23, and the Northeast 1/4 of Section 22, Township 38 North, Range 2 East*

ADDITIONAL LEGAL DESCRIPTION ON PAGE(S) ____ OF DOCUMENT.

ASSESSOR'S TAX/PARCEL NUMBER(S): *380223195333, 380223191352, 380215533063, 380215494049, 380215520100, 380215471064, 380215457041, 380215468032, 380215478022, 380223124302*

**STATEMENT OF INTENT
TO COLLECT CONNECTION FEE
LCS 50-04**

1. This document imposes a deferred assessment on property owners to compensate the City of Bellingham for construction of certain public facilities.
2. The public facility involved here is described as: Installation of 4,193 linear feet of 18" sewer main and appurtenances along Marine Drive from the intersection of Bennett Drive Northwesterly to Williamson Way.
3. NOTICE IS HEREBY GIVEN that, pursuant to RCW 35.92 and Bellingham Municipal Code Section 15.08.230 (water) or 15.12.170 (sewer), the City of Bellingham will


charge and collect a minimum of \$84.7532 per linear foot of property frontage for each service hereinafter connected to the above described improvement. Parcels of property which may be subject to these charges are indicated on the attached page of this document by legal description and/or a map thereof.

4. If payment of the above charge is made within 90 days of the date of recordation of this document, then no interest shall be charged. For payments subsequent to that time, interest will be charged on the amount in paragraph 3, computed in accordance with applicable Bellingham Municipal Code Section 15.08.230(A) (water)/15.12.175 (sewer).
5. Information regarding this document or the amount to be charged may be obtained from the City Department of Public Works.

DATED this 19th day of January, 2004 by the CITY OF BELLINGHAM.

Approved as to Form:

Lee C. Reardon
Office of the City Attorney



Attest:

Therese Hol
Finance Director

Richard E. McKinley
Department Head CAB

STATE OF WASHINGTON }
COUNTY OF WHATCOM } SS

I CERTIFY that I know or have satisfactory evidence that **MARK ASMUNDSON** is the person who appeared before me, and said person acknowledged that he signed this instrument, on oath stated that he was authorized to execute the instrument and acknowledged it as the **Mayor** of the **CITY OF BELLINGHAM** to be the free and voluntary act of such party for the uses and purposes mentioned in the instrument.

JAN 19 2005



DATED Renie B Hill

SIGNATURE OF NOTARY PUBLIC

RENIE B. HILL
NAME PRINTED


Notary Public
TITLE

10 Sept 2007
MY APPOINTMENT EXPIRES

STATE OF WASHINGTON }
COUNTY OF WHATCOM } SS

I CERTIFY that I know or have satisfactory evidence that **THERESE HOLM** is the person who appeared before me, and said person acknowledged that he signed this instrument, on oath stated that he was authorized to execute the instrument and acknowledged it as the **Finance Director** of the **CITY OF BELLINGHAM** to be the free and voluntary act of such party for the uses and purposes mentioned in the instrument.

19 January, 2005
DATED





Martha L Hagen
SIGNATURE OF NOTARY PUBLIC


MARTHA L HAGEN
NAME PRINTED

Notary Public
TITLE

29 April 2007
MY APPOINTMENT EXPIRES



 Latecomer Boundary



LCS 50-04

Director of Public Works

Richard C. McKinley

Whatcom County Water Dist. #2

Phone: 360-733-5770
Fax : 360-671-4912

1615 Bayon Rd
Bellingham, WA 98225

19 October 2023

ABC Recycling
8081 Meadow Avenue
Burnaby, BC V3N 2V9

Subject: Water Availability at 741 Marine Dr.

Dear Steve,

Whatcom County Water District #2 can provide water to the above property subject to confirmation of potable water and fire flow requirements subject to water availability.

Currently a new $\frac{3}{4}$ inch potable service connection including 1 equivalent residential unit (ERU) per parcel is:

General Facilities Fee \$4,500.00

Connection Fee (minimum) \$2,000.00

All connection costs over \$2,000.00 will be paid by the customer.

All Permit Fess will be paid by the customer.

Whatcom County Water Dist. #2 will install the meter at the property line and requires the property owner to install a shut off valve "One Foot" beyond the meter box before service is turned on.

The current minimum charge to install a fire hydrant if requested is \$8,500.00.

All connection costs over the \$8,500.00 will be paid by the customer,

All Permit Fess will be paid by the customer.

Any engineering and design required by the district or permitting will be paid by the customer, in addition to the above costs.

If you have any further questions, please call me.

Sincerely Yours,

Lorrie Whitfield

Office Manager

From: [Steve Holan](#)
To: [Scott Goodall](#); [Brandon Hausmann](#)
Cc: [Andy Anthony](#); [Viral Patel](#); [Steve Shinn](#)
Subject: FW: Water Availability - 741 Marine Dr.
Date: Thursday, October 19, 2023 10:47:11 AM
Attachments: [image001.png](#)
[image002.png](#)
[image003.png](#)
[image004.png](#)
[image005.png](#)
[WD2 water availability letter to ABC.doc](#)

Good morning,

Please see the updated letter dated today for the Water Availability to the site.

Thank you,

Steven Holan, CRSP

Director, Health, Safety, and Environment

T: 604-522-9727 **C:** 604-219-0040

From: Lorrie Whitfield <wccd2@qwestoffice.net>
Sent: Thursday, October 19, 2023 10:41 AM
To: Steve Holan <steve.holan@abcrecycling.com>
Cc: Dave Olson <dave@watersystems-services.net>
Subject: RE: Water Availability - 741 Marine Dr.

CAUTION: This email originated from outside the organization. Do not click links or open attachments unless you recognize the sender and know the content is safe.

Good Morning Steve,

Attached you will find an updated letter per your request.

The letter is *District* information only and will not meet county building & codes requirements.

Sincerely,

Lorrie Whitfield

Office Manager
Whatcom County Water #2
360-733-5770

From: Steve Holan <steve.holan@abcrecycling.com>
Sent: Wednesday, October 18, 2023 4:14 PM

To: wcd2@qwestoffice.net

Cc: Andy Anthony <andy.anthony@abcrecycling.com>; Brandon Hausmann <brandon@alpineengineer.com>; Steve.Shinn <Steve.Shinn@abcrecycling.com>; Scott Goodall <scott@bold-impact.com>

Subject: RE: Water Availability - 741 Marine Dr.

Good afternoon,

In late 2020 we received the attached letter regarding water availability at 741 Marine Dr. As the document is a few years old, would it be possible to confirm the previous details in this letter, update the letter for 2023 and have it signed?

Please let me know any additional details that we could provide, or information required so we can obtain an updated water availability letter for 741 Marine Dr.

Thank you,

Steven Holan, CRSP

Director, Health, Safety, and Environment

T: 604-522-9727 **C:** 604-219-0040



8081 Meadow Avenue, Burnaby, BC V3N 2V9

*"We exist to preserve the world's resources,
building thriving communities by accelerating metal recycling"*

The information shared in this e-mail contains privileged and confidential information which is the property of ABC Recycling Ltd, and its affiliated companies. The email is intended solely for the use of the intended recipient(s). Unauthorized use or disclosure of this information is prohibited. If you are not an intended recipient, please immediately notify ABC Recycling Ltd and destroy any copies of this email. Receipt of this e-mail shall not be deemed a waiver by ABC Recycling Ltd of any privilege or the confidential nature of the information.